

Tartan Foam Extinguisher

MT-X5910410

- EN3 Approved
- Cream colour identification for foam



- The perfect choice for Class A and B fires.
- AFFF for rapid control and extinction of hydrocarbon fires.
- AFFF spray foam gives wide coverage for maximum firefighting performance.
- Supplied factory filled with wall bracket.



Foam Extinguisher	9 litre AFFF
Part number	MT-X5910410
Diameter (mm)	Ø 185
Height (mm)	597
Empty weight (kg)	4.3
Full weight (kg)	14
Volume (L)	10.7
Filling charge	9 Litre 3% AFFF foam solution
Temperature range (°C)	+5°C ~ +60°C
Working pressure at 20°C (bar)	15
Test pressure (bar)	27
Material	DC01, Mild Steel
Fire rating for Class A and B fires	21A 233B
Packing specification (mm)	195 x 195 x 620
Paint Finish	RED RAL3000
Discharge Time (seconds)	34.7
Range (m)	3.7



Licence No. KM646583



INTERNATIONAL SALES
Angus Fire Ltd
 Angus House, Haddenham Business Park,
 Pegasus Way, Haddenham, Aylesbury, HP17 8LB, UK
 Tel: +44 (0)1844 293600 • Fax: +44 (0)1844 293664

UK SALES
Angus Fire Ltd
 Station Road, Bentham, Lancaster, LA2 7NA, UK
 Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 264180

Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.