

# Tartan CO<sub>2</sub> Extinguishers

**2kg MT-X0603010**

**5kg MT-X0509010**

- EN3 Approved
- Black colour identification for CO<sub>2</sub>



- Highly effective on electrical fires (Class E) and Class B fires.
- Clean, safe and powerful for minimal damage to property.
- Steel alloy cylinder tested to 250 bar.
- 5 kg model with hose and horn applicator.
- Supplied factory filled with bracket.



CO <sub>2</sub> Extinguisher	2kg	5kg
Part number	MT-X0603010	MT-X0509010
Diameter (mm)	Ø 103	Ø 135.8
Height (mm)	578	753
Empty weight (kg)	3.6	7.9
Full weight (kg)	6.4	13.5
Volume (L)	3.0	7.5
Filling charge	2kg CO <sub>2</sub>	5kg CO <sub>2</sub>
Temperature range (°C)	-30°C ~ +60°C	-30°C ~ +60°C
Working pressure at 20°C (bar)	174	174
Test pressure (bar)	250	250
Material	34Cr m04, Steel Alloy	34Cr m04, Steel Alloy
Fire rating	34B	89B
Packing specification (mm)	170 x 120 x 595	170 x 145 x 770
Paint Finish	RED RAL3000	RED RAL3000
Discharge Time (seconds)	9.4	15.6
Range (m)	2.9	3.0



**INTERNATIONAL SALES**  
**Angus Fire Ltd**  
 Angus House, Haddenham Business Park,  
 Pegasus Way, Haddenham, Aylesbury, HP17 8LB, UK  
 Tel: +44 (0)1844 293600 • Fax: +44 (0)1844 293664

**UK SALES**  
**Angus Fire Ltd**  
 Station Road, Bentham, Lancaster, LA2 7NA, UK  
 Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 264180

Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.

© Angus Fire  
 6826/1 01.16