

Tartan Dry Powder Extinguishers

2kg MT-X3208210

6kg MT-X3218210

9kg MT-X3226210

- EN3 Approved
- Blue colour identification for powder



- High performance dry powder models for rapid fire knockdown on a variety of risks.
- ABC multi-purpose powder for all round fire protection on Class A, B and C fires.
- 15 bar working pressure for greater application reach and improved initial fire knockdown.
- Supplied factory filled with wall bracket.



Dry Powder Extinguisher	2kg	6kg	9kg
Part number	MT-X3208210	MT-X3218210	MT-X3226210
Diameter (mm)	Ø 110	Ø 160	Ø 185
Height (mm)	363	512	540
Empty weight (kg)	1.13	2.82	3.77
Full weight (kg)	3.5	9.45	13.2
Volume (L)	2.35	7.6	10.2
Filling charge	2kg 40% ABC (EN15)	6kg 40% ABC (EN15)	9kg 40% ABC (EN15)
Temperature range (°C)	-30°C ~ +60°C	-30°C ~ +60°C	-30°C ~ +60°C
Working pressure at 20°C (bar)	15	15	15
Test pressure (bar)	27	27	27
Material	DC01, Mild Steel	DC01, Mild Steel	DC01, Mild Steel
Fire rating	13A 55B	34A 183B	43A 183B
Packing specification (mm)	345 x 260 x 390 / 6pcs	170 x 170 x 560	195 x 195 x 635
Paint Finish	RED RAL3000	RED RAL3000	RED RAL3000
Discharge Time (seconds)	11.6	13.1	17.8
Range (m)	4.2	5.1	5.6



Licence No. KM646583

INTERNATIONAL SALES

Angus Fire Ltd

Angus House, Haddenham Business Park,
Pegasus Way, Haddenham, Aylesbury, HP17 8LB, UK
Tel: +44 (0)1844 293600 • Fax: +44 (0)1844 293664

UK SALES

Angus Fire Ltd

Station Road, Bentham, Lancaster, LA2 7NA, UK
Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 264180

Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.

© Angus Fire
6827/1 01.16