

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture
Product name : Forexpan
Product code : FC 09 01

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Firefighting foam concentrate

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ANGUS FIRE Ltd
Station Road
Bentham LA2 7NA - United Kingdom
T +44 1524 264000 - F +441524 264180
general.enquiries@angusuk.co.uk - www.angusfire.co.uk

1.4. Emergency telephone number

Emergency number : T +44(0) 1524 264000 (Standard office hours: Monday to Friday 8:30am – 4:30pm GMT)
Contact person: EH&S Manager

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 1 H318
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS05

Signal word (CLP) : Danger
Hazardous ingredients : Sodium laureth sulfate; Disodium Isodecyl Sulfosuccinate
Hazard statements (CLP) : H315 - Causes skin irritation
H318 - Causes serious eye damage
H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (CLP) : P264 - Wash hands thoroughly after handling
P280 - Wear eye protection, protective clothing, protective gloves
P302+P352 - IF ON SKIN: Wash with plenty of water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P332+P313 - If skin irritation occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse

2.3. Other hazards

PBT: not relevant – no registration required

Forexpan

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

vPvB: not relevant – no registration required

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-(2-Butoxyethoxy)ethanol	(CAS-No.) 112-34-5 (EC-No.) 203-961-6 (EC Index-No.) 603-096-00-8 (REACH-no) 01-2119475104-44	25 - 50	Eye Irrit. 2, H319
Sodium laureth sulfate	(CAS-No.) 68891-38-3 (EC-No.) 500-234-8 (REACH-no) 01211948863916	10 - 25	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Disodium Isodecyl Sulfosuccinate	(CAS-No.) 37294-49-8 (EC-No.) 253-452-8 (REACH-no) 01-2120100165-75	1 - 25	Eye Dam. 1, H318
Ethane-1,2-diol	(CAS-No.) 107-21-1 (EC-No.) 203-473-3 (EC Index-No.) 603-027-00-1 (REACH-no) 01-2119456816-28	4 - 10	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
1-Dodecanol	(CAS-No.) 112-53-8 (EC-No.) 203-982-0	0.1 - 4	Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1-Tetradecanol	(CAS-No.) 112-72-1 (EC-No.) 204-000-3	0.1 - 1	Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Morpholine substance with a Community workplace exposure limit	(CAS-No.) 110-91-8 (EC-No.) 203-815-1 (EC Index-No.) 613-028-00-9	< 0.05	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Sodium laureth sulfate	(CAS-No.) 68891-38-3 (EC-No.) 500-234-8 (REACH-no) 01211948863916	(5 =<C < 10) Eye Irrit. 2, H319 (10 =<C < 100) Eye Dam. 1, H318

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: No specific measures are necessary. This product is a fire extinguishing medium.
Unsuitable extinguishing media	: Not applicable.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
-------------	-------------------

Forexpan

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.3. Advice for firefighters

Firefighting instructions : Not applicable.
Protection during firefighting : Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

8. Exposure controls/personal protection. 13. Disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Wear recommended personal protective equipment. Read and follow manufacturer's recommendations. Handle in accordance with good industrial hygiene and safety procedures.
Hygiene measures : Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Keep container tightly closed. Store at temperatures not exceeding 60°C (140°F) (intermittent). Protect from freezing. Keep/Store away from incompatible materials.

7.3. Specific end use(s)

Firefighting foam concentrate.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-(2-Butoxyethoxy)ethanol (112-34-5)		
EU	Local name	2-(2-Butoxyethoxy)ethanol
EU	IOELV TWA (mg/m ³)	67.5 mg/m ³
EU	IOELV TWA (ppm)	10 ppm
EU	IOELV STEL (mg/m ³)	101.2 mg/m ³
EU	IOELV STEL (ppm)	15 ppm
Belgium	Limit value (mg/m ³)	67.5 mg/m ³ (2-(2-Butoxyéthoxy)éthanol; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	10 ppm (2-(2-Butoxyéthoxy)éthanol; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m ³)	101.2 mg/m ³ (2-(2-Butoxyéthoxy)éthanol; Belgium; Short time value)
Belgium	Short time value (ppm)	15 ppm (2-(2-Butoxyéthoxy)éthanol; Belgium; Short time value)
France	Local name	2-(2-butoxyéthoxy)éthanol
France	VME (mg/m ³)	67.5 mg/m ³
France	VME (ppm)	10 ppm
France	VLE (mg/m ³)	101.2 mg/m ³
France	VLE (ppm)	15 ppm
France	Note (FR)	Valeurs réglementaires indicatives
Netherlands	Grenswaarde TGG 8H (mg/m ³)	50 mg/m ³ (2-(2-butoxyethoxy)ethanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	7.4 ppm (2-(2-butoxyethoxy)ethanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)

Forexpan

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-(2-Butoxyethoxy)ethanol (112-34-5)		
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	100 mg/m ³ 2-(2-butoxyethoxy)ethanol; Netherlands; Short time value; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (ppm)	15 ppm 2-(2-butoxyethoxy)ethanol; Netherlands; Short time value; Public occupational exposure limit value)
United Kingdom	WEL TWA (mg/m ³)	67.5 mg/m ³ 2-(2-Butoxyethoxy)ethanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	10 ppm 2-(2-Butoxyethoxy)ethanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m ³)	101.2 mg/m ³ 2-(2-Butoxyethoxy)ethanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	15 ppm 2-(2-Butoxyethoxy)ethanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH	ACGIH TWA (ppm)	10 ppm (Diethylene glycol monobutyl ether; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor)
Ethane-1,2-diol (107-21-1)		
EU	IOELV TWA (mg/m ³)	52 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
EU	IOELV STEL (mg/m ³)	104 mg/m ³
EU	IOELV STEL (ppm)	40 ppm
Belgium	Limit value (mg/m ³)	52 mg/m ³ (Ethylèneglycol (en aérosol); Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	20 ppm (Ethylèneglycol (en aérosol); Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m ³)	104 mg/m ³ (Ethylèneglycol (en aérosol); Belgium; Short time value)
Belgium	Short time value (ppm)	40 ppm (Ethylèneglycol (en aérosol); Belgium; Short time value)
France	VME (mg/m ³)	52 mg/m ³ (Ethylèneglycol (vapeur); France; Time-weighted average exposure limit 8 h; VRI: Valeur réglementaire indicative)
France	VME (ppm)	20 ppm (Ethylèneglycol (vapeur); France; Time-weighted average exposure limit 8 h; VRI: Valeur réglementaire indicative)
France	VLE (mg/m ³)	104 mg/m ³ (Ethylèneglycol (vapeur); France; Short time value; VRI: Valeur réglementaire indicative)
France	VLE (ppm)	40 ppm (Ethylèneglycol (vapeur); France; Short time value; VRI: Valeur réglementaire indicative)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	52 mg/m ³ (Ethaan-1,2-diol (damp); Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; damp; Ethaan-1,2-diol (druppels); 10 mg/m ³ ; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; druppels)
Netherlands	Grenswaarde TGG 8H (ppm)	20 ppm (Ethaan-1,2-diol (damp); Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; damp; Ethaan-1,2-diol (druppels); 3.9 ppm; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; druppels)
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	104 mg/m ³ (Ethaan-1,2-diol (damp); Netherlands; Short time value; Public occupational exposure limit value; damp)
Netherlands	Grenswaarde TGG 15MIN (ppm)	40 ppm (Ethaan-1,2-diol (damp); Netherlands; Short time value; Public occupational exposure limit value; damp)
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ Ethane-1,2-diol particulate; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005); Ethane-1,2-diol vapour; 52 mg/m ³ ; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)

Forexpan

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethane-1,2-diol (107-21-1)		
United Kingdom	WEL TWA (ppm)	20 ppm Ethane-1,2-diol vapour; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m ³)	104 mg/m ³ Ethane-1,2-diol vapour; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	40 ppm Ethane-1,2-diol vapour; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH	ACGIH Ceiling (mg/m ³)	100 mg/m ³ (Ethylene glycol; USA; Momentary value; TLV - Adopted Value)
Morpholine (110-91-8)		
EU	IOELV TWA (mg/m ³)	36 mg/m ³ (Morpholine; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV TWA (ppm)	10 ppm (Morpholine; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV STEL (mg/m ³)	72 mg/m ³ (Morpholine; EU; Short time value; Indicative occupational exposure limit value)
EU	IOELV STEL (ppm)	20 ppm (Morpholine; EU; Short time value; Indicative occupational exposure limit value)
Belgium	Limit value (mg/m ³)	36 mg/m ³ (Morpholine; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	10 ppm (Morpholine; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m ³)	72 mg/m ³ (Morpholine; Belgium; Short time value)
Belgium	Short time value (ppm)	20 ppm (Morpholine; Belgium; Short time value)
France	VME (mg/m ³)	36 mg/m ³ (Morpholine; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
France	VME (ppm)	10 ppm (Morpholine; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
France	VLE (mg/m ³)	72 mg/m ³ (Morpholine; France; Short time value; VRC: Valeur réglementaire contraignante)
France	VLE (ppm)	20 ppm (Morpholine; France; Short time value; VRC: Valeur réglementaire contraignante)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	36 mg/m ³ (Morpholine; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	9.9 ppm (Morpholine; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	72 mg/m ³ (Morpholine; Netherlands; Short time value; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (ppm)	20 ppm (Morpholine; Netherlands; Short time value; Public occupational exposure limit value)
United Kingdom	WEL TWA (mg/m ³)	36 mg/m ³ Morpholine; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	10 ppm Morpholine; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m ³)	72 mg/m ³ Morpholine; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	20 ppm Morpholine; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH	ACGIH TWA (ppm)	20 ppm (Morpholine; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)

Forexpan

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2. Exposure controls

Appropriate engineering controls:

Ensure adequate ventilation. Follow the exposure limits given on this material safety data sheet.

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves (butyl rubber)

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing. Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment (A2/P2).

Thermal hazard protection:

Wear thermal protective clothing, when necessary.

Environmental exposure controls:

Contain spills. Prevent releases. Observe national regulations on emissions. Ensure all national/local regulations are observed.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Light yellow.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: 8 - 9.5
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: -13 °C
Boiling point	: No data available
Flash point	: > 100 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.03 - 1.05
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: 20 mm ² /s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable and non reactive under normal conditions of use, storage and transport.

Forexpan

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Incompatible materials. Extremely high or low temperatures.

10.5. Incompatible materials

Alkali metals. Oxidizing agent. Water reactive substances.

10.6. Hazardous decomposition products

Carbon oxides. Sulphur oxides. Nitrogen oxides (NOx). Sodium oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

1-Dodecanol (112-53-8)	
LD50 oral rat	12800 mg/kg
LD50 dermal rabbit	15000 mg/kg
LC50 inhalation rat (mg/l)	> 1.5 mg/l/4h
1-Tetradecanol (112-72-1)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
2-(2-Butoxyethoxy)ethanol (112-34-5)	
LD50 oral rat	5660 mg/kg (Rat)
LD50 dermal rabbit	2764 mg/kg (Rabbit; Experimental value; OECD 402 : acute dermal toxicity)
Ethane-1,2-diol (107-21-1)	
LD50 oral rat	> 5000 mg/kg (Rat; Study on Literature)
Morpholine (110-91-8)	
LD50 oral rat	1420 mg/kg (Rat)
LD50 dermal rabbit	500 mg/kg (Rabbit)

Skin corrosion/irritation : Causes skin irritation.
pH: 8 - 9.5

Serious eye damage/irritation : Causes serious eye damage.
pH: 8 - 9.5

Respiratory or skin sensitisation : Not classified

Additional information : Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified
Based on available data, the classification criteria are not met

Carcinogenicity : Not classified
Additional information : Based on available data, the classification criteria are not met

Reproductive toxicity : Not classified
Additional information : Based on available data, the classification criteria are not met

STOT-single exposure : Not classified
Additional information : Based on available data, the classification criteria are not met

STOT-repeated exposure : Not classified
Additional information : Based on available data, the classification criteria are not met

Aspiration hazard : Not classified
Additional information : Based on available data, the classification criteria are not met

Forexpan	
Viscosity, kinematic	20 mm ² /s

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Forexpan

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects.

1-Dodecanol (112-53-8)	
LC50 fish 1	1.01 mg/l (96 h; Pimephales promelas)
LC50 fish 2	0.1855 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	320 mg/l (48 h; Daphnia magna)
EC50 Daphnia 2	0.8 mg/l (96 h; Crustacea)
Threshold limit algae 1	0.3 mg/l (96 h; Scenedesmus subspicatus)

1-Tetradecanol (112-72-1)	
LC50 fish 1	> 1000 mg/l (96 h; Pisces)
LC50 fish 2	> 1 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Semi-static system; Fresh water; Experimental value)
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)
EC50 Daphnia 1	3.2 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Semi-static system; Fresh water; Experimental value)
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h)
Threshold limit algae 1	> 10 mg/l (EL50; Equivalent or similar to OECD 201; 96 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value)

2-(2-Butoxyethoxy)ethanol (112-34-5)	
LC50 fish 1	1300 mg/l (96 h; Lepomis macrochirus)
LC50 fish 2	1805 mg/l (48 h; Leuciscus idus)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	2850 mg/l (24 h; Daphnia magna; GLP)
EC50 Daphnia 2	> 100 mg/l (48 h; Daphnia magna)
TLM fish 1	10 - 100,96 h; Pisces
TLM other aquatic organisms 1	10 - 100,96 h
Threshold limit other aquatic organisms 1	10 - 100,96 h
Threshold limit algae 1	53 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	>= 100 mg/l (96 h; Scenedesmus subspicatus)

Ethane-1,2-diol (107-21-1)	
LC50 fish 1	53000 mg/l (96 h; Pimephales promelas; Static system)
LC50 fish 2	40761 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Static system)
EC50 Daphnia 1	> 10000 mg/l (24 h; Daphnia magna)
Threshold limit algae 1	> 10000 mg/l (168 h; Scenedesmus quadricauda)
Threshold limit algae 2	2000 mg/l (192 h; Microcystis aeruginosa)

Morpholine (110-91-8)	
LC50 fish 1	180 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss); Fresh water (not alkaline)
LC50 fish 2	350 ppm 96 h; Lepomis macrochirus; Fresh water (not alkaline)
LC50 other aquatic organisms 1	100 - 1000 mg/l (96 h)
EC50 Daphnia 1	119 mg/l (24 h; Daphnia magna)
Threshold limit algae 1	4.1 mg/l (192 h; Scenedesmus quadricauda)
Threshold limit algae 2	1.7 mg/l (168 h; Microcystis aeruginosa)

12.2. Persistence and degradability

Forexpan	
Persistence and degradability	The product is readily biodegradable. May cause long-term adverse effects in the environment.
Biochemical oxygen demand (BOD)	0.2 g O ₂ /g substance (5 days)
Chemical oxygen demand (COD)	1.1 g O ₂ /g substance
Biodegradation	90 % (28 days)
1-Dodecanol (112-53-8)	
Persistence and degradability	Readily biodegradable in water.
ThOD	3.09 g O ₂ /g substance
BOD (% of ThOD)	0.3 % ThOD
1-Tetradecanol (112-72-1)	
Persistence and degradability	Readily biodegradable in water.

Forexpan

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1-Tetradecanol (112-72-1)	
ThOD	3.13 g O ₂ /g substance
2-(2-Butoxyethoxy)ethanol (112-34-5)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.25 g O ₂ /g substance
Chemical oxygen demand (COD)	2.08 g O ₂ /g substance
ThOD	2.173 g O ₂ /g substance
BOD (% of ThOD)	0.11
Ethane-1,2-diol (107-21-1)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.47 g O ₂ /g substance
Chemical oxygen demand (COD)	1.24 g O ₂ /g substance
ThOD	1.29 g O ₂ /g substance
BOD (% of ThOD)	0.36
Morpholine (110-91-8)	
Biochemical oxygen demand (BOD)	0.02 g O ₂ /g substance
ThOD	2.6 g O ₂ /g substance
BOD (% of ThOD)	0.009
12.3. Bioaccumulative potential	
Forexpan	
Bioaccumulative potential	The product is not expected to bioaccumulate.
1-Dodecanol (112-53-8)	
Log Pow	5.13
1-Tetradecanol (112-72-1)	
BCF other aquatic organisms 1	> 23000
BCF other aquatic organisms 2	33900 (BCF)
Log Pow	5.94 - 6.11
2-(2-Butoxyethoxy)ethanol (112-34-5)	
BCF fish 1	0.46 (QSAR)
Log Pow	0.56 (Experimental value)
Bioaccumulative potential	Low bioaccumulation potential.
Ethane-1,2-diol (107-21-1)	
BCF fish 1	10 (72 h; <i>Leuciscus idus</i>)
BCF other aquatic organisms 1	0.21 - 0.6 (<i>Procambarus</i> sp.; Chronic)
BCF other aquatic organisms 2	190 (24 h; Algae)
Log Pow	-1.34 (Experimental value)
Bioaccumulative potential	Low bioaccumulation potential.
Morpholine (110-91-8)	
BCF fish 1	< 2.3 (<i>Cyprinus carpio</i> ; Chronic)
BCF fish 2	< 2.8 (<i>Oryzias latipes</i> ; Chronic)
Log Pow	-2.55
12.4. Mobility in soil	
1-Dodecanol (112-53-8)	
Surface tension	0.03 N/m
1-Tetradecanol (112-72-1)	
Surface tension	0.024 N/m
Log Koc	log Koc,4.71; Experimental value
2-(2-Butoxyethoxy)ethanol (112-34-5)	
Surface tension	0.034 N/m (25 °C)
Ethane-1,2-diol (107-21-1)	
Surface tension	0.048 N/m (20 °C)

Forexpan

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Morpholine (110-91-8)	
Surface tension	0.0375 N/m

12.5. Results of PBT and vPvB assessment

Forexpan	
PBT: not relevant – no registration required	
vPvB: not relevant – no registration required	

12.6. Other adverse effects

Other adverse effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.
European List of Waste (LoW) code : 16 03 05* - organic wastes containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : Not applicable
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : Not applicable
UN-No. (ADN) : Not applicable
UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable

14.3. Transport hazard class(es)

ADR
Transport hazard class(es) (ADR) : Not applicable

IMDG
Transport hazard class(es) (IMDG) : Not applicable

IATA
Transport hazard class(es) (IATA) : Not applicable

ADN
Transport hazard class(es) (ADN) : Not applicable

RID
Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

Forexpan

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

- Air transport

No data available

- Inland waterway transport

No data available

- Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Forexpan - 2-(2-Butoxyethoxy)ethanol - Ethane-1,2-diol - Morpholine
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Morpholine
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Forexpan - 2-(2-Butoxyethoxy)ethanol - Ethane-1,2-diol - Morpholine
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Forexpan
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	Morpholine
55. 2-(2-butoxyethoxy)ethanol (DEGBE)	2-(2-Butoxyethoxy)ethanol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 2, significant hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Forexpan

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS EU (REACH Annex II) - Angus Fire

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product