

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name or designation of the mixture	Tridol ATF 3/6 LT
Registration number	-
Synonyms	None.
SDS number	-
Product code	140-10
Issue date	24-July-2012
Version number	02
Revision date	03-December-2014
Supersedes date	24-July-2012

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Firefighting foam concentrate.
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet**Supplier**

Company name	Angus Fire Ltd
Address	Station Road Bentham, Lancashire, LA2 7NA
Telephone	0044 (0)15 2426 4000
e-mail	general.enquiries@angusuk.co.uk
Contact person	EH&S Manager

1.4. Emergency telephone number 0044 (0)15 2426 4000 (Standard office hours: Monday to Friday 8:30am - 4:30pm GMT)

Section 2: Hazards identification**2.1. Classification of the substance or mixture**

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

This preparation does not meet the criteria for classification according to Directive 1999/45/EC as amended.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards		
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.

Hazard summary

Physical hazards	Not classified for physical hazards.
Health hazards	Not classified for health hazards. However, occupational exposure to the mixture or substance(s) may cause adverse health effects.
Environmental hazards	Not classified for hazards to the environment.
Specific hazards	May cause skin and eye irritation. May cause respiratory tract irritation. May cause damage to the kidneys. A few cases of sensitisation have been reported. May cause central nervous system effects.
Main symptoms	Symptoms can include irritation, redness, scratching of the cornea, and tearing. Symptoms may include redness, oedema, drying, defatting and cracking of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

2.2. Label elements**Label according to Regulation (EC) No. 1272/2008 as amended**

Contains:	2-(2-Butoxyethoxy)-Ethanol, Sodium alkylethoxy sulphate
------------------	---

Hazard pictograms



Signal word Warning
Hazard statements H319 - Causes serious eye irritation.

Precautionary statements

Prevention P280 - Wear eye/face protection.
P264 - Wash thoroughly after handling.
Response P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists, get medical advice/attention.
Storage Not available.
Disposal P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information Not applicable.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

Section 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Ethylene glycol	20-<25	107-21-1 203-473-3	-	603-027-00-1	#
Classification:	DSD: Xn;R22 CLP: Acute Tox. 4;H302				
2-(2-Butoxyethoxy)-Ethanol	5 - < 10	112-34-5 203-961-6	-	603-096-00-8	#
Classification:	DSD: Xi;R36 CLP: Eye Irrit. 2;H319				
Sodium alkylethoxy sulphate	1 - < 3	96130-61-9	-	-	
Classification:	DSD: Xi;R38-41 CLP: Skin Irrit. 2;H315, Eye Dam. 1;H318				

#: This substance has been assigned Community workplace exposure limit(s).

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.
The full text for all R- and H-phrases is displayed in section 16.

Section 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Move injured person into fresh air and keep person calm under observation. Get medical attention if discomfort persists.
Skin contact Wash the skin immediately with soap and water. Get medical attention if irritation develops and persists.
Eye contact Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention if irritation develops and persists.
Ingestion Immediately rinse mouth and drink plenty of water. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed Symptoms can include irritation, redness, scratching of the cornea, and tearing. Symptoms may include redness, oedema, drying, defatting and cracking of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

Section 5: Firefighting measures

General fire hazards

Product is an extinguishing medium. It does not burn or support combustion.

5.1. Extinguishing media

Suitable extinguishing media

No specific measures are required as this product is a fire extinguishing medium.

Unsuitable extinguishing media

Not applicable.

5.2. Special hazards arising from the substance or mixture

Not a fire hazard.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus, operated in positive pressure mode and full protective clothing must be worn in case of fire.

Special fire fighting procedures

No specific precautions.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid contact with skin and eyes. Avoid inhalation of mists or aerosols. Provide adequate ventilation. Wear protective clothing as described in section 8 of this safety data sheet.

For emergency responders

Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

For large (industrial) releases, prevent spill from entering a waterway.

6.3. Methods and material for containment and cleaning up

Absorb spillage with suitable absorbent material. Collect and dispose of spillage as indicated in Section 13.

6.4. Reference to other sections

For personal protection, see section 8.
For waste disposal, see section 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes. Wear appropriate personal protective equipment. Wash hands after handling. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store at temperature below 40°C. Store above freezing. Store away from incompatible materials.

7.3. Specific end use(s)

Firefighting foam concentrate.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List Components

2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)

Type

Value

MAK

97,5 mg/m3

STEL

10 ppm
101,2 mg/m3
15 ppm

Ethylene glycol (CAS 107-21-1)

Ceiling

52 mg/m3

MAK

20 ppm
26 mg/m3
10 ppm

Belgium. Exposure Limit Values. Components

2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)

Type

Value

Form

STEL

101,2 mg/m3

TWA

15 ppm
67,5 mg/m3
10 ppm

Ethylene glycol (CAS 107-21-1)

STEL

104 mg/m3
40 ppm

Aerosol

Aerosol

Belgium. Exposure Limit Values.

Components	Type	Value	Form
	TWA	52 mg/m3	Aerosol
		20 ppm	Aerosol

Czech Republic. OELs. Government Decree 361

Components	Type	Value
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	Ceiling	100 mg/m3
Ethylene glycol (CAS 107-21-1)	TWA	70 mg/m3
	Ceiling	100 mg/m3
	TWA	50 mg/m3

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value	Form
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	VLE	101,2 mg/m3	
Ethylene glycol (CAS 107-21-1)	VME	15 ppm	
		67,5 mg/m3	
		10 ppm	
Ethylene glycol (CAS 107-21-1)	VLE	104 mg/m3	Vapor.
		40 ppm	Vapor.
			52 mg/m3
		20 ppm	Vapor.

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	TWA	67 mg/m3
Ethylene glycol (CAS 107-21-1)	TWA	10 ppm
		26 mg/m3
		10 ppm

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	AGW	67 mg/m3
Ethylene glycol (CAS 107-21-1)	AGW	10 ppm
		26 mg/m3
		10 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value	Form
Ethylene glycol (CAS 107-21-1)	STEL	125 mg/m3	Vapor.
	TWA	50 ppm	Vapor.
125 mg/m3		Vapor.	
50 ppm		Vapor.	

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Ethylene glycol (CAS 107-21-1)	STEL	104 mg/m3
	TWA	52 mg/m3

Italy. OELs

Components	Type	Value	
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	STEL	101,2 mg/m3	
Ethylene glycol (CAS 107-21-1)	TWA	15 ppm	
		67,5 mg/m3	
		10 ppm	
Ethylene glycol (CAS 107-21-1)	STEL	104 mg/m3	
		40 ppm	
			52 mg/m3
		20 ppm	

Netherlands. OELs (binding)

Components	Type	Value	Form
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	STEL	100 mg/m ³	
Ethylene glycol (CAS 107-21-1)	TWA	50 mg/m ³	
	STEL	104 mg/m ³	Vapor.
	TWA	52 mg/m ³ 10 mg/m ³	Vapor. Mist.

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value	Form
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	TLV	68 mg/m ³	
Ethylene glycol (CAS 107-21-1)	Ceiling	10 ppm	
		25 ppm	Vapor.
	TLV	10 mg/m ³	Dust.

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Components	Type	Value
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	STEL	100 mg/m ³
Ethylene glycol (CAS 107-21-1)	TWA	67 mg/m ³
	STEL	50 mg/m ³
	TWA	15 mg/m ³

Russian Federation. Hygiene Norm GN 2.2.5.1313-03. Executive No. 76 of 30 April 2003. Maximum allowable concentration (MAC) of harmful substances in the air of working zones, as amended.

Components	Type	Value	Form
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	Ceiling	10 mg/m ³	Aerosol
Ethylene glycol (CAS 107-21-1)	Ceiling	10 mg/m ³	Vapor and aerosol.
	TWA	5 mg/m ³	Vapor and aerosol.

Spain. Occupational Exposure Limits

Components	Type	Value
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	STEL	101,2 mg/m ³
Ethylene glycol (CAS 107-21-1)	TWA	15 ppm
		67,5 mg/m ³
	STEL	10 ppm 104 mg/m ³
	TWA	40 ppm
		52 mg/m ³ 20 ppm

Sweden. Occupational Exposure Limit Values

Components	Type	Value
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	STEL	200 mg/m ³
Ethylene glycol (CAS 107-21-1)	TWA	30 ppm
		100 mg/m ³
	STEL	15 ppm 50 mg/m ³
	TWA	20 ppm
		25 mg/m ³ 10 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	STEL	101,2 mg/m ³
Ethylene glycol (CAS 107-21-1)	TWA	15 ppm
		67 mg/m ³ 10 ppm
	STEL	52 mg/m ³

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
	TWA	20 ppm 26 mg/m ³ 10 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	STEL	101,2 mg/m ³	
	TWA	15 ppm 67,5 mg/m ³ 10 ppm	
Ethylene glycol (CAS 107-21-1)	STEL	104 mg/m ³	Vapor.
	TWA	40 ppm 52 mg/m ³ 10 mg/m ³ 20 ppm	Vapor. Vapor. Particulate. Vapor.

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived No Effect Level (DNEL)

Components	Type	Route	Value	Form
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	Workers	Dermal	20 mg/kg	Long term exposure systemic effects
		Inhalation	67,5 mg/m ³	Long term exposure local effects
		Inhalation	67,5 mg/m ³	Long term exposure systemic effects
		Inhalation	101,2 mg/m ³	Acute exposure local effects
Ethylene glycol (CAS 107-21-1)	Workers	Dermal	106 mg/l	Long term exposure systemic effects
		Inhalation	35 mg/m ³	Long term exposure systemic effects

Predicted no effect concentrations (PNECs)

Components	Type	Route	Value	Form
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)	Aqua (freshwater)	Not applicable	1 mg/l	
	Aqua (intermittent releases)	Not applicable	3,9 mg/l	
	Aqua (marine water)	Not applicable	0,1 mg/l	
	Sediment (freshwater)	Not applicable	4 mg/kg	
	Sediment (marine water)	Not applicable	0,4 mg/kg	
	Soil	Not applicable	0,4 mg/kg	
Ethylene glycol (CAS 107-21-1)	STP	Not applicable	200 mg/l	
	Aqua (freshwater)	Not applicable	10 mg/l	
	Aqua (intermittent releases)	Not applicable	10 mg/l	
	Aqua (marine water)	Not applicable	1 mg/l	
	Sediment (freshwater)	Not applicable	20,9 mg/kg	
	Soil	Not applicable	1,53 mg/kg	
	STP	Not applicable	199 mg/l	

8.2. Exposure controls

Appropriate engineering controls Ensure adequate ventilation, especially in confined areas. Observe occupational exposure limits and minimise the risk of exposure.

Individual protection measures, such as personal protective equipment

General information Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Wear approved safety goggles.

Skin protection

- Hand protection	Wear suitable gloves. Butyl rubber gloves are recommended. Suitable gloves can be recommended by the glove supplier.
- Other	Wear suitable protective clothing.
Respiratory protection	In case of inadequate ventilation: Use respiratory equipment with combination filter, type A2/P2.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Handle in accordance with good industrial hygiene and safety practices. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Contain spills and prevent releases and observe national regulations on emissions. Environmental manager must be informed of all major spillages.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Colour	Pale yellow.
Odour	Organic.
Odour threshold	Not available.
pH	6,5 - 8
Melting point/freezing point	Not available.
Initial boiling point and boiling range	100 °C (212 °F) at 760 mmHg
Flash point	> 98 °C (> 208,4 °F) Pensky-Martens Closed Cup
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	1,02
Relative density temperature	20 °C (68 °F)
Solubility(ies)	Miscible with water in all proportions.
Partition coefficient (n-octanol/water)	Not available.
Decomposition temperature	Not available.
Viscosity	Not applicable.
Explosive properties	Not available.
Oxidizing properties	Not available.
9.2. Other information	No relevant additional information available.

Section 10: Stability and reactivity

10.1. Reactivity	The product is stable and non reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Stable at normal conditions.
10.3. Possibility of hazardous reactions	Hazardous polymerisation does not occur.
10.4. Conditions to avoid	Contact with incompatible materials. Excessive heat. Freezing (Product properties are unaffected).
10.5. Incompatible materials	Alkali metals. Strong oxidising agents. Water reactive materials.
10.6. Hazardous decomposition products	Carbon oxides. Sulphur oxides. Nitrogen oxides (NOx). Sodium oxides. Hydrogen fluoride.

Section 11: Toxicological information

General information	The information in this section is for the individual ingredients that are expected to contribute to the potential health effects of this product.
----------------------------	--

Information on likely routes of exposure

Ingestion	May cause discomfort if swallowed.
Inhalation	Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
Skin contact	May cause skin irritation.
Eye contact	Causes serious eye irritation.

Symptoms Symptoms can include irritation, redness, scratching of the cornea, and tearing. Symptoms may include redness, oedema, drying, defatting and cracking of the skin.

11.1. Information on toxicological effects

Acute toxicity Causes serious eye irritation. Prolonged contact may cause dryness of the skin.

Components	Species	Test results
2-(2-Butoxyethoxy)-Ethanol (CAS 112-34-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	2700 mg/kg
<i>Oral</i>		
LD50	Rat	4500 mg/kg
Ethylene glycol (CAS 107-21-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	9530 mg/kg
<i>Oral</i>		
LD50	Rat	5,89 g/kg

Skin corrosion/irritation Prolonged contact may cause dryness of the skin.

Serious eye damage/irritation May cause eye irritation. Exposed may experience eye tearing, redness, and discomfort.

Respiratory sensitisation No data available.

Skin sensitisation Not a skin sensitiser.

Germ cell mutagenicity No data available.

Carcinogenicity No data available.

Reproductive toxicity No data available.

Specific target organ toxicity - single exposure No data available.

Specific target organ toxicity - repeated exposure No data available.

Aspiration hazard No data available.

Mixture versus substance information None known.

Other information Persons with pre-existing skin disorders may be more susceptible to the effects of the product. May cause damage to the kidneys. Prolonged contact may cause dryness of the skin. May damage the unborn child if very large amounts are swallowed.

Section 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test results
Ethylene glycol (CAS 107-21-1)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 8050 mg/l, 96 hours

12.2. Persistence and degradability No data available.

12.3. Bioaccumulative potential The product is not expected to bioaccumulate.

Partition coefficient n-octanol/water (log Kow)

Ethylene glycol	-1,36
2-(2-Butoxyethoxy)-Ethanol	0,56

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

Mobility in general	The product is water soluble and may spread in water systems.
12.5. Results of PBT and vPvB assessment	No data available.
12.6. Other adverse effects	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of waste and residues in accordance with local authority requirements.
Contaminated packaging	Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	16 03 05* Waste codes should be assigned by the user based on the application for which the product was used.
Disposal methods/information	Dispose of waste and residues in accordance with local authority requirements.

Section 14: Transport information

ADR

The product is not covered by international regulation on the transport of dangerous goods.

RID

The product is not covered by international regulation on the transport of dangerous goods.

ADN

The product is not covered by international regulation on the transport of dangerous goods.

IATA

The product is not covered by international regulation on the transport of dangerous goods.

IMDG

The product is not covered by international regulation on the transport of dangerous goods.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 on persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Commission Decision 2000/479/EC on the implementation of a European pollutant emission register (EPER)

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA

Not listed.

Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations

Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

Section 16: Other information

List of abbreviations

DNEL: Derived No-Effect Level. PNEC: Predicted No-Effect Concentration. PBT: Persistent, bioaccumulative and toxic. vPvB: Very Persistent and very Bioaccumulative.

References

HSDB® - Hazardous Substances Data Bank
Registry of Toxic Effects of Chemical Substances (RTECS)

Information on evaluation method leading to the classification of mixture
Full text of any statements or R-phrases and H-statements under Sections 2 to 15

The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12.

R22 Harmful if swallowed.
R36 Irritating to eyes.
R38 Irritating to skin.
R41 Risk of serious damage to eyes.
H302 - Harmful if swallowed.
H315 - Causes skin irritation.
H318 - Causes serious eye damage.
H319 - Causes serious eye irritation.

Training information

Follow training instructions when handling this material.

Disclaimer

This information is based on our current knowledge and is believed to be correct as of the date issued. The information is intended to describe the product for the purposes of health, safety and environmental requirements only and no warranty, express or implied, is made. It should also not be construed as guaranteeing any specific property of the product. In addition, information obtained from a database is subject to change and may not be as current as the information in the MSDS available directly from Angus Fire.