

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 03/02/2017 Revision date: 22/08/2017 Supersedes: 09/05/2017 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Tridol^{C6} S6 LT

Product code : FNC 03 08

Type of product : Firefighting foam concentrate (AFFF)

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial

For professional use only

Use of the substance/mixture : Firefighting foam concentrate

Uses advised against
 No additional information available

1.3. Details of the supplier of the safety data sheet

ANGUS FIRE Ltd Station Road

Bentham LA2 7NA - United Kingdom T +44 1524 264000 - F +441524 264180

general.enquiries@angusuk.co.uk - www.angusfire.co.uk

1.4. Emergency telephone number

Emergency number : T +44(0) 1524 264000 (Standard office hours: Monday to Friday 8:30am – 4:30pm GMT)

Contact person: EH&S Manager

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4

H302

Specific target organ toxicity — Repeated exposure, Category 2

H373

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :





GHS07 GHS

Signal word (CLP) : Warning
Hazardous ingredients : Ethane-1,2-diol

Hazard statements (CLP) : H302 - Harmful if swallowed

H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (if

swallowed)

Precautionary statements (CLP) : P264 - Wash hands thoroughly after handling

P270 - Do not eat, drink or smoke when using this product P301+P312 - IF SWALLOWED: Call a doctor if you feel unwell

P314 - Get medical advice/attention if you feel unwell

P330 - Rinse mouth

P501 - Dispose in a safe manner in accordance with local/national regulations

2.3. Other hazards

PBT: not relevant – no registration required vPvB: not relevant – no registration required

22/08/2017 EN (English) 1/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethane-1,2-diol	(CAS-No.) 107-21-1 (EC-No.) 203-473-3 (EC Index-No.) 603-027-00-1 (REACH-no) 01-2119456816-28	25 - 50	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
2-(2-Butoxyethoxy)ethanol	(CAS-No.) 112-34-5 (EC-No.) 203-961-6 (EC Index-No.) 603-096-00-8 (REACH-no) 01-2119475104-44	4 - 10	Eye Irrit. 2, H319
2-methyl-2,4-pentanediol substance with a Community workplace exposure limit	(CAS-No.) 107-41-5 (EC-No.) 203-489-0 (EC Index-No.) 603-053-00-3 (REACH-no) 01-2119539582-35	0.05 - 0.1	Skin Irrit. 2, H315 Eye Irrit. 2, H319

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed

by warm water rinse.

First-aid measures after ingestion : Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a POISON

CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes damage to organs (kidneys) (if swallowed).

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : No specific measures are necessary. This product is a fire extinguishing medium.

Unsuitable extinguishing media : Not applicable.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard.

5.3. Advice for firefighters

Firefighting instructions : Not applicable.

Protection during firefighting : Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

22/08/2017 EN (English) 2/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.4. Reference to other sections

8. Exposure controls/personal protection. 13. Disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

 Avoid contact with skin and eyes. Wear recommended personal protective equipment. Read and follow manufacturer's recommendations. Handle in accordance with good industrial hygiene and safety procedures.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in original container. Keep container tightly closed. Store at temperatures not exceeding 60°C (140°F) (intermittent). Protect from freezing. Keep/Store away from incompatible materials.

7.3. Specific end use(s)

Firefighting foam concentrate.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-(2-Butoxyethoxy)eth	anol (112-34-5)	
EU	Local name	2-(2-Butoxyethoxy)ethanol
EU	IOELV TWA (mg/m³)	67.5 mg/m³
EU	IOELV TWA (ppm)	10 ppm
EU	IOELV STEL (mg/m³)	101.2 mg/m³
EU	IOELV STEL (ppm)	15 ppm
Belgium	Limit value (mg/m³)	67.5 mg/m³ (2-(2-Butoxyéthoxy)éthanol; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	10 ppm (2-(2-Butoxyéthoxy)éthanol; Belgium; Time- weighted average exposure limit 8 h)
Belgium	Short time value (mg/m³)	101.2 mg/m³ (2-(2-Butoxyéthoxy)éthanol; Belgium; Short time value)
Belgium	Short time value (ppm)	15 ppm (2-(2-Butoxyéthoxy)éthanol; Belgium; Short time value)
France	Local name	2-(2-butoxyéthoxy)éthanol
France	VME (mg/m³)	67.5 mg/m³
France	VME (ppm)	10 ppm
France	VLE (mg/m³)	101.2 mg/m³
France	VLE (ppm)	15 ppm
France	Note (FR)	Valeurs règlementaires indicatives
Netherlands	Grenswaarde TGG 8H (mg/m³)	50 mg/m³ (2-(2-butoxyethoxy)ethanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	7.4 ppm (2-(2-butoxyethoxy)ethanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	100 mg/m³ (2-(2-butoxyethoxy)ethanol; Netherlands; Short time value; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (ppm)	15 ppm (2-(2-butoxyethoxy)ethanol; Netherlands; Short time value; Public occupational exposure limit value)
United Kingdom	WEL TWA (mg/m³)	67.5 mg/m³ 2-(2-Butoxyethoxy)ethanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	10 ppm 2-(2-Butoxyethoxy)ethanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m³)	101.2 mg/m³ 2-(2-Butoxyethoxy)ethanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	15 ppm 2-(2-Butoxyethoxy)ethanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH	ACGIH TWA (ppm)	10 ppm (Diethylene glycol monobutyl ether; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor)

22/08/2017 EN (English) 3/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-methyl-2,4-pentaned EU	, ,	122 mg/m3
	IOELV TWA (mg/m³)	123 mg/m³
EU	IOELV TWA (ppm)	25 ppm
EU	IOELV STEL (mg/m³)	123 mg/m³
EU	IOELV STEL (ppm)	25 ppm
Belgium	Limit value (mg/m³)	123 mg/m³ (1,6-Hexanediol; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	25 ppm (1,6-Hexanediol; Belgium; Time-weighted average exposure limit 8 h)
France	VLE (mg/m³)	125 mg/m³ (Hexylèneglycol; France; Short time value; VL: Valeur non réglementaire indicative)
France	VLE (ppm)	25 ppm (Hexylèneglycol; France; Short time value; VL Valeur non réglementaire indicative)
United Kingdom	WEL TWA (mg/m³)	123 mg/m³ 2-Methylpentane-2,4-diol; United Kingdom Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	25 ppm 2-Methylpentane-2,4-diol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m³)	123 mg/m³ 2-Methylpentane-2,4-diol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	25 ppm 2-Methylpentane-2,4-diol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH	ACGIH Ceiling (ppm)	25 ppm (Hexylene glycol; USA; Momentary value; TL\ - Adopted Value)
Ethane-1,2-diol (107-21	I-1)	
EU	IOELV TWA (mg/m³)	52 mg/m³
EU	IOELV TWA (ppm)	20 ppm
EU	IOELV STEL (mg/m³)	104 mg/m³
EU	IOELV STEL (ppm)	40 ppm
Belgium	Limit value (mg/m³)	52 mg/m³ (Ethylèneglycol (en aérosol); Belgium; Time- weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	20 ppm (Ethylèneglycol (en aérosol); Belgium; Time- weighted average exposure limit 8 h)
Belgium	Short time value (mg/m³)	104 mg/m³ (Ethylèneglycol (en aérosol); Belgium; Short time value)
Belgium	Short time value (ppm)	40 ppm (Ethylèneglycol (en aérosol); Belgium; Short time value)
France	VME (mg/m³)	52 mg/m³ (Ethylèneglycol (vapeur); France; Time- weighted average exposure limit 8 h; VRI: Valeur réglementaire indicative)
France	VME (ppm)	20 ppm (Ethylèneglycol (vapeur); France; Time- weighted average exposure limit 8 h; VRI: Valeur réglementaire indicative)
France	VLE (mg/m³)	104 mg/m³ (Ethylèneglycol (vapeur); France; Short time value; VRI: Valeur réglementaire indicative)
France	VLE (ppm)	40 ppm (Ethylèneglycol (vapeur); France; Short time value; VRI: Valeur réglementaire indicative)
Netherlands	Grenswaarde TGG 8H (mg/m³)	52 mg/m³ (Ethaan-1,2-diol (damp); Netherlands; Time weighted average exposure limit 8 h; Public occupational exposure limit value; damp; Ethaan-1,2-diol (druppels); 10 mg/m³; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; druppels)
Netherlands	Grenswaarde TGG 8H (ppm)	20 ppm (Ethaan-1,2-diol (damp); Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; damp; Ethaan-1,2-diol (druppels); 3.9 ppm; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; druppels)
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	104 mg/m³ (Ethaan-1,2-diol (damp); Netherlands; Short time value; Public occupational exposure limit value; damp)

22/08/2017 EN (English) 4/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethane-1,2-diol (107-21-1)		
Netherlands	Grenswaarde TGG 15MIN (ppm)	40 ppm (Ethaan-1,2-diol (damp); Netherlands; Short time value; Public occupational exposure limit value; damp)
United Kingdom	WEL TWA (mg/m³)	10 mg/m³ Ethane-1,2-diol particulate; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005); Ethane-1,2-diol vapour; 52 mg/m³; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	20 ppm Ethane-1,2-diol vapour; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m³)	104 mg/m³ Ethane-1,2-diol vapour; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	40 ppm Ethane-1,2-diol vapour; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH	ACGIH Ceiling (mg/m³)	100 mg/m³ (Ethylene glycol; USA; Momentary value; TLV - Adopted Value)

8.2. Exposure controls

Appropriate engineering controls:

Ensure adequate ventilation. Follow the exposure limits given on this material safety data sheet.

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves (butyl rubber)

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment (A2/P2).

Thermal hazard protection:

Wear thermal protective clothing, when necessary.

Environmental exposure controls:

Contain spills. Prevent releases. Observe national regulations on emissions. Ensure all national/local regulations are observed.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

Physical state : Liquid
Colour : Amber.
Odour : Characteristic.
Odour threshold : No data available

pH : 6.6 - 7.6

Relative evaporation rate (butylacetate=1) : No data available Melting point : No data available

Freezing point : -19 °C

Boiling point : No data available

Flash point : > 100 °C

Auto-ignition temperature : No data available

22/08/2017 EN (English) 5/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

: No data available Decomposition temperature Flammability (solid, gas) : Non flammable. Vapour pressure : No data available Relative vapour density at 20 °C : No data available Relative density : No data available : 1.02 - 1.06 Density Solubility : No data available Log Pow : No data available Viscosity, kinematic : 2.9 mm²/s Viscosity, dynamic : No data available Explosive properties : No data available

Oxidising properties : No data available Explosive limits : No data available

Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity

The product is stable and non reactive under normal conditions of use, storage and transport.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Conditions to avoid

Incompatible materials. Extremely high or low temperatures.

Incompatible materials

Additional information

Germ cell mutagenicity

Additional information

Carcinogenicity

Alkali metals. Oxidizing agent. Water reactive substances.

Hazardous decomposition products

Carbon oxides. Sulphur oxides. Hydrogen fluoride. Nitrogen oxides (NOx). Sodium oxides.

SECTION 11: Toxicological informati	on
11.1. Information on toxicological effects	
Acute toxicity	: Oral: Harmful if swallowed.
ATE CLP (oral)	500 mg/kg bodyweight
2-(2-Butoxyethoxy)ethanol (112-34-5)	
LD50 oral rat	5660 mg/kg (Rat)
LD50 dermal rabbit	2764 mg/kg (Rabbit; Experimental value; OECD 402 : acute dermal toxicity)
2-methyl-2,4-pentanediol (107-41-5)	
LD50 oral rat	3700 mg/kg (Rat; OECD 420; Experimental value; > 2000 mg/kg bodyweight; Rat)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Experimental value; OECD 402: acute dermal toxicity)
LD50 dermal rabbit	> 8000 mg/kg (Rabbit)
Ethane-1,2-diol (107-21-1)	
LD50 oral rat	> 5000 mg/kg (Rat; Study on Literature)
Skin corrosion/irritation	: Not classified
	pH: 6.6 - 7.6
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified
	pH: 6.6 - 7.6
Respiratory or skin sensitisation	: Not classified

22/08/2017 EN (English) 6/10

: Not classified

: Not classified

: Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

: Based on available data, the classification criteria are not met

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reproductive toxicity : Not classified

Additional information : Based on available data, the classification criteria are not met

STOT-single exposure : Not classified

Additional information : Based on available data, the classification criteria are not met

STOT-repeated exposure : May cause damage to organs (kidneys) through prolonged or repeated exposure (if

swallowed).

Aspiration hazard : Not classified

Additional information : Based on available data, the classification criteria are not met

Tridol^{C6} S6 LT
Viscosity, kinematic 2.9 mm²/s

Potential adverse human health effects and

symptoms

: Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

2-(2-Butoxyethoxy)ethanol (112-34-5)	
LC50 fish 1	1300 mg/l (96 h; Lepomis macrochirus)
LC50 fish 2	1805 mg/l (48 h; Leuciscus idus)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	2850 mg/l (24 h; Daphnia magna; GLP)
EC50 Daphnia 2	> 100 mg/l (48 h; Daphnia magna)
TLM fish 1	10 - 100,96 h; Pisces
TLM other aquatic organisms 1	10 - 100,96 h
Threshold limit other aquatic organisms 1	10 - 100,96 h
Threshold limit algae 1	53 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	>= 100 mg/l (96 h; Scenedesmus subspicatus)

2-methyl-2,4-pentanediol (107-41-5)	
LC50 fish 1	12800 mg/l (96 h; Lepomis macrochirus)
LC50 fish 2	9450 mg/l (96 h; Oncorhynchus mykiss)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	5410 mg/l (48 h; Daphnia magna)
EC50 Daphnia 2	3300 mg/l (48 h; Daphnia pulex)
Threshold limit other aquatic organisms 1	10 - 100,96 h
Threshold limit algae 1	> 429 mg/l (72 h; Pseudokirchneriella subcapitata)

Ethane-1,2-diol (107-21-1)	
LC50 fish 1	53000 mg/l (96 h; Pimephales promelas; Static system)
LC50 fish 2	40761 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Static stystem)
EC50 Daphnia 1	> 10000 mg/l (24 h; Daphnia magna)
Threshold limit algae 1	> 10000 mg/l (168 h; Scenedesmus quadricauda)
Threshold limit algae 2	2000 mg/l (192 h; Microcystis aeruginosa)

12.2. Persistence and degradability

2-(2-Butoxyethoxy)ethanol (112-34-5)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.25 g O₂/g substance
Chemical oxygen demand (COD)	2.08 g O₂/g substance
ThOD	2.173 g O₂/g substance
BOD (% of ThOD)	0.11

2-methyl-2,4-pentanediol (107-41-5)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.02 g O₂/g substance
Chemical oxygen demand (COD)	2.2 g O₂/g substance
ThOD	2.3 g O₂/g substance
BOD (% of ThOD)	0.01

22/08/2017 EN (English) 7/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethane-1,2-diol (107-21-1)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.47 g O₂/g substance
Chemical oxygen demand (COD)	1.24 g O₂/g substance
ThOD	1.29 g O₂/g substance
BOD (% of ThOD)	0.36
2.3. Bioaccumulative potential	
Tridol ^{C6} S6 LT	
Rigaccumulative notential	The product is not expected to bioaccumulate

Tridol ^{c6} S6 LT	
Bioaccumulative potential	The product is not expected to bioaccumulate.
2-(2-Butoxyethoxy)ethanol (112-34-5)	
BCF fish 1	0.46 (QSAR)
Log Pow	0.56 (Experimental value)
Bioaccumulative potential	Low bioaccumulation potential.
2-methyl-2,4-pentanediol (107-41-5)	
Log Pow	0.58 (QSAR)
Bioaccumulative potential	Low bioaccumulation potential.
Ethane-1,2-diol (107-21-1)	
BCF fish 1	10 (72 h; Leuciscus idus)
BCF other aquatic organisms 1	0.21 - 0.6 (Procambarus sp.; Chronic)
BCF other aquatic organisms 2	190 (24 h; Algae)
Log Pow	-1.34 (Experimental value)
Bioaccumulative potential	Low bioaccumulation potential.

12.4. Mobility in soil

2-(2-Butoxyethoxy)ethanol (112-34-5)	
Surface tension	0.034 N/m (25 °C)
2-methyl-2,4-pentanediol (107-41-5)	
Surface tension	0.033 N/m
Log Koc	Koc,Other; 1; Calculated value
Ethane-1,2-diol (107-21-1)	
Surface tension	0.048 N/m (20 °C)

12.5. Results of PBT and vPvB assessment

Tridol ^{co} S6 LT	
	PBT: not relevant – no registration required
	vPvB: not relevant – no registration required

12.6. Other adverse effects

Other adverse effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

European List of Waste (LoW) code : 16 03 05* - organic wastes containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number	
UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable

22/08/2017 EN (English) 8/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

adn

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

- Air transport

No data available

- Inland waterway transport

No data available

- Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:	
3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Tridol ^{C6} S6 LT - 2-(2-Butoxyethoxy)ethanol - 2-methyl-2,4-pentanediol - Ethane-1,2-diol
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects. 3.9 and 3.10	Tridol ^{C6} S6 LT - 2-(2-Butoxyethoxy)ethanol - 2-methyl-2,4-pentanediol - Ethane-1,2-diol

22/08/2017 EN (English) 9/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

55. 2-(2-butoxyethoxy)ethanol (DEGBE)	2-(2-Butoxyethoxy)ethanol
33. 2 (2 batoxyctrioxy)ctriarior (BEGBE)	2 (2 Datoxyctrioxy)ctriarior

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

National regulations 15.1.2.

Germany

: Water hazard class (WGK) 2, significant hazard to waters (Classification according to VwVwS, VwVwS Annex reference

Annex 4)

12th Ordinance Implementing the Federal

Immission Control Act - 12.BImSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Borstvoeding

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Vruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Ontwikkeling

: None of the components are listed : None of the components are listed

: None of the components are listed

: None of the components are listed

: None of the components are listed

Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the

product

Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE Data sources

COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H373	May cause damage to organs through prolonged or repeated exposure

SDS EU (REACH Annex II) - Angus Fire

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

22/08/2017 EN (English) 10/10