

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture
Product name : Tridol^{C6} Ultra 1/3
Product code : FNC 03 58
Type of product : Firefighting foam concentrate (AR-AFFF)

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Firefighting foam concentrate

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ANGUS FIRE Ltd
Station Road
Bentham LA2 7NA - United Kingdom
T +44 1524 264000 - F +441524 264180
general.enquiries@angusuk.co.uk - www.angusfire.co.uk

1.4. Emergency telephone number

Emergency number : T +44(0) 1524 264000 (Standard office hours: Monday to Friday 8:30am – 4:30pm GMT)
Contact person: EH&S Manager

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315

Serious eye damage/eye irritation, Category 1 H318

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

Signal word (CLP) : Danger
Hazardous ingredients : Sodium decyl sulfate; Alkyl polyglycoside C8-10
Hazard statements (CLP) : H315 - Causes skin irritation
H318 - Causes serious eye damage
Precautionary statements (CLP) : P264 - Wash hands thoroughly after handling
P280 - Wear protective clothing, protective gloves, eye protection
P302+P352 - IF ON SKIN: Wash with plenty of water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P332+P313 - If skin irritation occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse

2.3. Other hazards

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

Tridol^{C6} Ultra 1/3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-methyl-2,4-pentanediol	(CAS-No.) 107-41-5 (EC-No.) 203-489-0 (EC Index-No.) 603-053-00-3 (REACH-no) 01-2119539582-35	10 - 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Sodium octyl sulfate	(CAS-No.) 142-31-4 (EC-No.) 205-535-5 (REACH-no) 01-2119966154-35	1 - 10	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Sodium decyl sulfate	(CAS-No.) 142-87-0 (EC-No.) 205-568-5 (REACH-no) 01-2119489461-32	1 - 4	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Alkyl polyglycoside C8-10	(CAS-No.) 68515-73-1 (EC-No.) 500-220-1 (REACH-no) 01-2119488530-36	1 - 4	Eye Dam. 1, H318
Fluorosurfactant blend	(CAS-No.) Proprietary	< 4	Aquatic Chronic 2, H411
Ethane-1,2-diol substance with a Community workplace exposure limit	(CAS-No.) 107-21-1 (EC-No.) 203-473-3 (EC Index-No.) 603-027-00-1 (REACH-no) 01-2119456816-28	0.1 - 1	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
2-(2-Butoxyethoxy)ethanol substance with a Community workplace exposure limit	(CAS-No.) 112-34-5 (EC-No.) 203-961-6 (EC Index-No.) 603-096-00-8 (REACH-no) 01-2119475104-44	< 1	Eye Irrit. 2, H319

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: No specific measures are necessary. This product is a fire extinguishing medium.
Unsuitable extinguishing media	: Not applicable.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
-------------	-------------------

5.3. Advice for firefighters

Firefighting instructions	: Not applicable.
Protection during firefighting	: Not applicable.

Tridol^{C6} Ultra 1/3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

8. Exposure controls/personal protection. 13. Disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Wear recommended personal protective equipment. Read and follow manufacturer's recommendations. Handle in accordance with good industrial hygiene and safety procedures.

Hygiene measures : Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Keep container tightly closed. Store at temperatures not exceeding 60°C (140°F) (intermittent). Protect from freezing. Keep/Store away from incompatible materials.

7.3. Specific end use(s)

Firefighting foam concentrate.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-methyl-2,4-pentanediol (107-41-5)		
EU	IOELV TWA (mg/m ³)	123 mg/m ³
EU	IOELV TWA (ppm)	25 ppm
EU	IOELV STEL (mg/m ³)	123 mg/m ³
EU	IOELV STEL (ppm)	25 ppm
Belgium	Limit value (mg/m ³)	123 mg/m ³ (1,6-Hexanediol; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	25 ppm (1,6-Hexanediol; Belgium; Time-weighted average exposure limit 8 h)
France	VLE (mg/m ³)	125 mg/m ³ (Hexylèneglycol; France; Short time value; VL: Valeur non réglementaire indicative)
France	VLE (ppm)	25 ppm (Hexylèneglycol; France; Short time value; VL: Valeur non réglementaire indicative)
United Kingdom	WEL TWA (mg/m ³)	123 mg/m ³ 2-Methylpentane-2,4-diol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	25 ppm 2-Methylpentane-2,4-diol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m ³)	123 mg/m ³ 2-Methylpentane-2,4-diol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	25 ppm 2-Methylpentane-2,4-diol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH	ACGIH Ceiling (ppm)	25 ppm (Hexylene glycol; USA; Momentary value; TLV - Adopted Value)
2-(2-Butoxyethoxy)ethanol (112-34-5)		
EU	Local name	2-(2-Butoxyethoxy)ethanol
EU	IOELV TWA (mg/m ³)	67.5 mg/m ³
EU	IOELV TWA (ppm)	10 ppm

Tridol^{C6} Ultra 1/3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-(2-Butoxyethoxy)ethanol (112-34-5)		
EU	IOELV STEL (mg/m ³)	101.2 mg/m ³
EU	IOELV STEL (ppm)	15 ppm
Belgium	Limit value (mg/m ³)	67.5 mg/m ³ (2-(2-Butoxyéthoxy)éthanol; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	10 ppm (2-(2-Butoxyéthoxy)éthanol; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m ³)	101.2 mg/m ³ (2-(2-Butoxyéthoxy)éthanol; Belgium; Short time value)
Belgium	Short time value (ppm)	15 ppm (2-(2-Butoxyéthoxy)éthanol; Belgium; Short time value)
France	Local name	2-(2-butoxyéthoxy)éthanol
France	VME (mg/m ³)	67.5 mg/m ³
France	VME (ppm)	10 ppm
France	VLE (mg/m ³)	101.2 mg/m ³
France	VLE (ppm)	15 ppm
France	Note (FR)	Valeurs réglementaires indicatives
Netherlands	Grenswaarde TGG 8H (mg/m ³)	50 mg/m ³ (2-(2-butoxyethoxy)ethanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	7.4 ppm (2-(2-butoxyethoxy)ethanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	100 mg/m ³ (2-(2-butoxyethoxy)ethanol; Netherlands; Short time value; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (ppm)	15 ppm (2-(2-butoxyethoxy)ethanol; Netherlands; Short time value; Public occupational exposure limit value)
United Kingdom	WEL TWA (mg/m ³)	67.5 mg/m ³ 2-(2-Butoxyethoxy)ethanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	10 ppm 2-(2-Butoxyethoxy)ethanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m ³)	101.2 mg/m ³ 2-(2-Butoxyethoxy)ethanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	15 ppm 2-(2-Butoxyethoxy)ethanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH	ACGIH TWA (ppm)	10 ppm (Diethylene glycol monobutyl ether; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor)
Ethane-1,2-diol (107-21-1)		
EU	IOELV TWA (mg/m ³)	52 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
EU	IOELV STEL (mg/m ³)	104 mg/m ³
EU	IOELV STEL (ppm)	40 ppm
Belgium	Limit value (mg/m ³)	52 mg/m ³ (Ethylèneglycol (en aérosol); Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	20 ppm (Ethylèneglycol (en aérosol); Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m ³)	104 mg/m ³ (Ethylèneglycol (en aérosol); Belgium; Short time value)
Belgium	Short time value (ppm)	40 ppm (Ethylèneglycol (en aérosol); Belgium; Short time value)
France	VME (mg/m ³)	52 mg/m ³ (Ethylèneglycol (vapeur); France; Time-weighted average exposure limit 8 h; VRI: Valeur réglementaire indicative)
France	VME (ppm)	20 ppm (Ethylèneglycol (vapeur); France; Time-weighted average exposure limit 8 h; VRI: Valeur réglementaire indicative)
France	VLE (mg/m ³)	104 mg/m ³ (Ethylèneglycol (vapeur); France; Short time value; VRI: Valeur réglementaire indicative)

Tridol^{C6} Ultra 1/3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethane-1,2-diol (107-21-1)		
France	VLE (ppm)	40 ppm (Ethylèneglycol (vapeur); France; Short time value; VRI: Valeur réglementaire indicative)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	52 mg/m ³ (Ethaan-1,2-diol (damp); Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; damp; Ethaan-1,2-diol (druppels); 10 mg/m ³ ; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; druppels)
Netherlands	Grenswaarde TGG 8H (ppm)	20 ppm (Ethaan-1,2-diol (damp); Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; damp; Ethaan-1,2-diol (druppels); 3.9 ppm; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; druppels)
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	104 mg/m ³ (Ethaan-1,2-diol (damp); Netherlands; Short time value; Public occupational exposure limit value; damp)
Netherlands	Grenswaarde TGG 15MIN (ppm)	40 ppm (Ethaan-1,2-diol (damp); Netherlands; Short time value; Public occupational exposure limit value; damp)
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ Ethane-1,2-diol particulate; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005); Ethane-1,2-diol vapour; 52 mg/m ³ ; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	20 ppm Ethane-1,2-diol vapour; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m ³)	104 mg/m ³ Ethane-1,2-diol vapour; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	40 ppm Ethane-1,2-diol vapour; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH	ACGIH Ceiling (mg/m ³)	100 mg/m ³ (Ethylene glycol; USA; Momentary value; TLV - Adopted Value)

8.2. Exposure controls

Appropriate engineering controls:

Ensure adequate ventilation. Follow the exposure limits given on this material safety data sheet.

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves (butyl rubber)

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing. Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment (A2/P2).

Tridol^{C6} Ultra 1/3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Thermal hazard protection:

Wear thermal protective clothing, when necessary.

Environmental exposure controls:

Contain spills. Prevent releases. Observe national regulations on emissions. Ensure all national/local regulations are observed.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Amber.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: 7.5 - 8.5
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: -8 °C
Boiling point	: No data available
Flash point	: > 100 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.01 - 1.05
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 1300 - 1900 cP
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable and non reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Incompatible materials. Extremely high or low temperatures.

10.5. Incompatible materials

Alkali metals. Oxidizing agent. Water reactive substances.

10.6. Hazardous decomposition products

Carbon oxides. Sulphur oxides. Hydrogen fluoride. Nitrogen oxides (NO_x). Sodium oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Tridol^{C6} Ultra 1/3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-methyl-2,4-pentanediol (107-41-5)	
LD50 oral rat	3700 mg/kg (Rat; OECD 420; Experimental value; > 2000 mg/kg bodyweight; Rat)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Experimental value; OECD 402: acute dermal toxicity)
LD50 dermal rabbit	> 8000 mg/kg (Rabbit)
2-(2-Butoxyethoxy)ethanol (112-34-5)	
LD50 oral rat	5660 mg/kg (Rat)
LD50 dermal rabbit	2764 mg/kg (Rabbit; Experimental value; OECD 402 : acute dermal toxicity)
Ethane-1,2-diol (107-21-1)	
LD50 oral rat	> 5000 mg/kg (Rat; Study on Literature)
Sodium decyl sulfate (142-87-0)	
LD50 oral rat	1950 mg/kg (Rat; Study Literature)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
Sodium octyl sulfate (142-31-4)	
LD50 oral rat	3200 mg/kg (Rat; OECD 423 : Acute oral toxicity - Class Method for acute toxicity; Literature study; >2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Experimental value; OECD 402 acute dermal toxicity)

Skin corrosion/irritation	: Causes skin irritation. pH: 7.5 - 8.5
Serious eye damage/irritation	: Causes serious eye damage. pH: 7.5 - 8.5
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

2-methyl-2,4-pentanediol (107-41-5)	
LC50 fish 1	12800 mg/l (96 h; Lepomis macrochirus)
LC50 fish 2	9450 mg/l (96 h; Oncorhynchus mykiss)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	5410 mg/l (48 h; Daphnia magna)
EC50 Daphnia 2	3300 mg/l (48 h; Daphnia pulex)
Threshold limit other aquatic organisms 1	10 - 100,96 h
Threshold limit algae 1	> 429 mg/l (72 h; Pseudokirchneriella subcapitata)
2-(2-Butoxyethoxy)ethanol (112-34-5)	
LC50 fish 1	1300 mg/l (96 h; Lepomis macrochirus)
LC50 fish 2	1805 mg/l (48 h; Leuciscus idus)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	2850 mg/l (24 h; Daphnia magna; GLP)
EC50 Daphnia 2	> 100 mg/l (48 h; Daphnia magna)
TLM fish 1	10 - 100,96 h; Pisces
TLM other aquatic organisms 1	10 - 100,96 h
Threshold limit other aquatic organisms 1	10 - 100,96 h

Tridol^{C6} Ultra 1/3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-(2-Butoxyethoxy)ethanol (112-34-5)	
Threshold limit algae 1	53 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	>= 100 mg/l (96 h; Scenedesmus subspicatus)
Ethane-1,2-diol (107-21-1)	
LC50 fish 1	53000 mg/l (96 h; Pimephales promelas; Static system)
LC50 fish 2	40761 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Static system)
EC50 Daphnia 1	> 10000 mg/l (24 h; Daphnia magna)
Threshold limit algae 1	> 10000 mg/l (168 h; Scenedesmus quadricauda)
Threshold limit algae 2	2000 mg/l (192 h; Microcystis aeruginosa)
Sodium decyl sulfate (142-87-0)	
LC50 fish 1	13 mg/l (LC50; JIS K0102-1986-71; 48 h; Cyprinus carpio; Static system; Fresh water; Experimental value)
EC50 Daphnia 1	470 mg/l (EC50; Other; 24 h; Daphnia magna; Fresh water)
Threshold limit algae 1	8.64 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
Threshold limit algae 2	0.95 mg/l (EC10; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
Sodium octyl sulfate (142-31-4)	
LC50 fish 1	> 100 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Danio rerio; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 1	> 100 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 1	> 511 mg/l (EC50; EU Method C.3; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Read-across)
Threshold limit algae 2	199 mg/l (EC10; EU Method C.3; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Read-across)

12.2. Persistence and degradability

2-methyl-2,4-pentanediol (107-41-5)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.02 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance
ThOD	2.3 g O ₂ /g substance
BOD (% of ThOD)	0.01
2-(2-Butoxyethoxy)ethanol (112-34-5)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.25 g O ₂ /g substance
Chemical oxygen demand (COD)	2.08 g O ₂ /g substance
ThOD	2.173 g O ₂ /g substance
BOD (% of ThOD)	0.11
Ethane-1,2-diol (107-21-1)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.47 g O ₂ /g substance
Chemical oxygen demand (COD)	1.24 g O ₂ /g substance
ThOD	1.29 g O ₂ /g substance
BOD (% of ThOD)	0.36
Sodium octyl sulfate (142-31-4)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

Tridol^{C6} Ultra 1/3	
Bioaccumulative potential	The product is not expected to bioaccumulate.
2-methyl-2,4-pentanediol (107-41-5)	
Log Pow	0.58 (QSAR)
Bioaccumulative potential	Low bioaccumulation potential.

Tridol^{C6} Ultra 1/3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-(2-Butoxyethoxy)ethanol (112-34-5)	
BCF fish 1	0.46 (QSAR)
Log Pow	0.56 (Experimental value)
Bioaccumulative potential	Low bioaccumulation potential.

Ethane-1,2-diol (107-21-1)	
BCF fish 1	10 (72 h; Leuciscus idus)
BCF other aquatic organisms 1	0.21 - 0.6 (Procambarus sp.; Chronic)
BCF other aquatic organisms 2	190 (24 h; Algae)
Log Pow	-1.34 (Experimental value)
Bioaccumulative potential	Low bioaccumulation potential.

Sodium decyl sulfate (142-87-0)	
Log Pow	0.71 (Estimated value)
Bioaccumulative potential	Low bioaccumulation potential.

Sodium octyl sulfate (142-31-4)	
Log Pow	-0.27 (Estimated value)
Bioaccumulative potential	Low bioaccumulation potential.

12.4. Mobility in soil

2-methyl-2,4-pentanediol (107-41-5)	
Surface tension	0.033 N/m
Log Koc	Koc,Other; 1; Calculated value

2-(2-Butoxyethoxy)ethanol (112-34-5)	
Surface tension	0.034 N/m (25 °C)

Ethane-1,2-diol (107-21-1)	
Surface tension	0.048 N/m (20 °C)

Sodium decyl sulfate (142-87-0)	
Surface tension	0.033 N/m (24 °C; 1 g/l)
Log Koc	log Koc,Other; 2.09 - 2.25; Experimental value

Sodium octyl sulfate (142-31-4)	
Surface tension	0.0584 N/m (21.5 °C; 1 g/l)
Log Koc	log Koc,Other; 1.88 - 2; Experimental value

12.5. Results of PBT and vPvB assessment

Tridol ^{C6} Ultra 1/3	
PBT: not relevant – no registration required	
vPvB: not relevant – no registration required	

12.6. Other adverse effects

Other adverse effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
 Ecology - waste materials : Avoid release to the environment.
 European List of Waste (LoW) code : 16 03 05* - organic wastes containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : Not applicable
 UN-No. (IMDG) : Not applicable
 UN-No. (IATA) : Not applicable
 UN-No. (ADN) : Not applicable
 UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable
 Proper Shipping Name (IMDG) : Not applicable

Tridol^{C6} Ultra 1/3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

- Air transport

No data available

- Inland waterway transport

No data available

- Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Tridol ^{C6} Ultra 1/3 - 2-methyl-2,4-pentanediol - 2-(2-Butoxyethoxy)ethanol - Ethane-1,2-diol
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Tridol ^{C6} Ultra 1/3 - 2-methyl-2,4-pentanediol - 2-(2-Butoxyethoxy)ethanol - Ethane-1,2-diol
55. 2-(2-butoxyethoxy)ethanol (DEGBE)	2-(2-Butoxyethoxy)ethanol

Tridol^{C6} Ultra 1/3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 2, significant hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS EU (REACH Annex II) - Angus Fire

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product