



Tridol^{C6} S1

Synthetic Aqueous Film-Forming Foam (AFFF) Concentrate

- Superior quality synthetic Aqueous Film-Forming Foam concentrate
- Stable foam blanket provides burnback resistance
- Suitable for use with fresh or sea water
- Compatible with standard proportioning and air aspirating foam making devices
- UL162 listed to -18°C (0°F)
- Film-forming for fast flame knockdown and extinguishment



Tridol^{C6} S1 is a superior quality synthetic Aqueous Film-Forming Foam (AFFF) concentrate for extinguishing and securing flammable hydrocarbon liquid fires.

Tridol^{C6} S1 is a unique combination of hydrocarbon and fluorochemical surface active agents. It produces a vapour-sealing aqueous film that spreads rapidly over the fuel surface to provide rapid control and extinguishment.

- Film-forming for fast flame knockdown and extinguishment.
- Burnback resistance and post-fire security.
- Foam blanket reseals when ruptured by personnel or equipment.

Applications

Tridol^{C6} S1 is used in high risk situations where hydrocarbons (such as crude oil, diesel and aviation kerosene) are stored, processed, or transported. It is used extensively on Rapid Intervention Vehicles (RIV) where fast extinguishment with limited quantities of foam is essential for saving life. Other applications include hydrocarbon storage tanks, process areas, warehouses, power stations and offshore platforms.

Tridol^{C6} S1 provides a vapour suppressing foam blanket on unignited hydrocarbon spills.

Approvals and Listings

Tridol^{C6} S1 is independently tested and certified to EN1568:2008 part 3.

Performance exceeds ICAO Level B fire performance and is certified to this performance level.

Tridol^{C6} S1 is audited and approved to Underwriters Laboratories UL162 (7th Edition).

Equipment

Tridol^{C6} S1 is intended for use at 1% (1 part concentrate to 99 parts water). Tridol^{C6} S1 is readily proportioned using conventional foam proportioning equipment.

Tridol^{C6} S1 can be used with air aspirating discharge devices and non-aspirating. Devices include low expansion branchpipes, monitors, top pourers, rimseal pourers, as well as water and foam sprinklers. Tridol^{C6} S1 is also suitable for base injection or sub-surface application systems.

Non-aspirated foam is suitable for shallow fuel fires and spill fires. Where a major fuel fire is involved, Angus Fire always recommends the use of aspirated foam where a stable foam blanket is essential.

Compatibility

Tridol^{C6} S1 is suitable for use in combination with:

- Soft or hard, fresh, brackish or sea water.
- Dry powder extinguishing agents either separately or as twin agent systems due to the C6 content.
- Expanded protein-based or synthetic foams for application to a fire in sequence or simultaneously.

Tridol[®] C6 S1

Synthetic Aqueous Film-Forming Foam (AFFF) Concentrate

Storage

Tridol[®] C6 S1 is exceptionally stable in long-term storage. A shelf-life of at least ten years can be expected if it is stored properly.

Environment & Disposal

As all 'C6' foams contain PFAS please refer to the product's Safety Data Sheet (SDS) and website for more information regarding the use, discharge and disposal of all firefighting foam products.

Product Quality

Tridol[®] C6 S1 production is closely controlled and is audited by UL in accordance with their approval system.

Angus Fire operates a quality management system which complies with the requirements of BS EN ISO 9001.

Typical Physico-Chemical Properties

Appearance		Amber Liquid
Specific gravity @ 20°C (68°F)		1.02 - 1.06
pH @ 20°C (68°F)		6.6 - 7.6
Viscosity @ 20°C (68°F)	mm ² sec ⁻¹	6
Maximum continuous storage temperature	°C (°F)	49 (120)
Maximum intermittent storage temperature	°C (°F)	60 (140)
Freezing point	°C (°F)	-21 (-5.8)
Effect of freeze/thaw		No loss of performance
UL Lowest use temperature	°C (°F)	-17.8 (0)

Typical Foam Properties

Foam generated using the U.K. Defence Standard DEF42-40 5 lpm branchpipe at 7 Bar pressure. Foam collected in a 1630 ml N.F.P.A. drainage pan.

Expansion ratio		≥8:1
25% drainage time	min/sec	≥ 2'40"

Typical Packing Specification

	Plastic Square	Plastic Square	Plastic Cylindrical	Plastic Cylindrical	Ecobulk MX
Capacity	25 litres	5 US gallons	200 litres	55 US gallons	1000 litres
Empty weight (kg)	1.2	0.8	9.0	9.0	70
Filled weight (kg)	27	21	217	225	1110
Dimensions (mm)	448 x 286 x 286	402 x 293 x 240	580 D x 922 H	580 D x 922 H	1200 L x 1000 W x 1160 H
Part number	FN0304G0P	FN0304T0P	FN0304J0P	FN0304W0P	FN0304L8



**EN1568:2008
Part 3**



EMERGENCY FOAM SERVICE Call +44 (0) 15242 61166 – 24 hours a day, every day

GENERAL SALES

Angus Fire Ltd

Station Road, Bentham, Lancaster, LA2 7NA, UK
Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 261580

Email: general.enquiries@angusuk.co.uk • Web: www.angusfire.co.uk

Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.

© Angus Fire 3715C6/4 10/21
Tridol[®] is a registered trademark of the Angus International group.