



## FP70<sup>C6</sup>

### FluoroProtein (FP) Fire Fighting Foam Concentrate

- A superior quality FluoroProtein Foam concentrate
- Unique formulation provides a tough, cohesive foam blanket with high resistance to heat
- UL162 listing
- Provides excellent sealing action on hot metal surfaces and foam blanket is re-sealed when ruptured
- Use in situations where hydrocarbons are processed, stored or transported
- Use at 3% at low expansion and with medium expansion a 6% induction rate is recommended
- Used with air aspirating discharge devices
- Suitable for use with fresh or sea water



FP70<sup>C6</sup> is a superior quality FluoroProtein (FP) fire fighting foam concentrate for extinguishing and securing flammable hydrocarbon liquid fires.

Its unique formulation is based on advanced protein foam technology. The protein base provides a tough cohesive foam blanket with high resistance to heat that quickly smothers, cools, and seals the risk. Fluorochemical surface active agents combined with the protein base increase the fluidity and fuel repellency of the foam.

- Excellent sealing action on hot metal surfaces.
- Foam blanket re-seals when ruptured by personnel or equipment.

#### Applications

FP70<sup>C6</sup> is the ideal fire fighting foam to use in situations where hydrocarbon fuels such as crude oil, gasoline, and fuel oils are stored, processed, or transported. It is used extensively by major world oil and petrochemical companies for tank fire protection.

FP70<sup>C6</sup> provides a vapour-suppressing foam blanket on unignited hydrocarbon spills.

#### Approvals and Listings

FP70<sup>C6</sup> has numerous approvals and UL Listings against Underwriters Laboratories Standard UL 162 (7th Edition).

Independently Tested and Certified to EN1568:2008 Part 3.

#### Equipment

FP70<sup>C6</sup> is intended for use at 3% at low expansion. With medium expansion equipment it can be used at 3% too, but for optimal results a 6% induction rate is recommended.

It is readily proportioned using conventional foam proportioning equipment such as portable and fixed foam proportioners.

FP70<sup>C6</sup> should be used with air aspirating discharge devices such as low expansion branchpipes, monitors and top pourer sets.

As with any foam, FP70<sup>C6</sup> is best applied gently on to the burning liquid surface. However, its exceptional resistance to fuel contamination enables it to withstand vigorous mixing with fuel. This makes it ideal for forceful application on to storage tank fires from ground-based mobile monitors or through base (sub-surface) injection systems.

#### Compatibility

FP70<sup>C6</sup> is suitable for use in combination with:

- Soft or hard, fresh, brackish or sea water.
- Dry powder extinguishing agents either separately or as twin agent systems.
- Expanded protein-based or synthetic foams for application to a fire in sequence or simultaneously.

# FP70<sup>C6</sup>

## FluoroProtein (FP) Fire Fighting Foam Concentrate

### Storage

FP70<sup>C6</sup> foam concentrate is exceptionally stable in long-term storage. A shelf-life of at least ten years can be expected if it is stored properly.

### Environment & Disposal

As all 'C6' foams contain PFAS please refer to the product's Safety Data Sheet (SDS) and website for more information regarding the use, discharge and disposal of all firefighting foam products.

### Reliability

FP70<sup>C6</sup> is produced to rigorous quality control standards to ensure consistent fire performance and excellent product reliability.

Angus Fire operates a quality management system which complies with the requirements of BS EN ISO 9001.

#### Typical Physico-Chemical Properties

Appearance		Dark Brown Liquid
Specific gravity @ 20°C (68°F)		1.14 - 1.18
pH @ 20°C (68°F)		6.6 - 7.6
Viscosity @ 20°C (68°F)	mm <sup>2</sup> sec <sup>-1</sup>	7.6 - 11.0
Maximum continuous storage temperature	°C (°F)	49 (120)
Maximum intermittent storage temperature	°C (°F)	60 (140)
Freezing Point	°C (°F)	-16 (3.2)
Effect of freeze/thaw		No loss of performance
UL Lowest use temperature	°C (°F)	-6.7 (20)

#### Typical Foam Properties

Foam generated using the U.K. Defence Standard DEF42-40 5 lpm branchpipe at 7 Bar pressure. Foam collected in a 1630 ml N.F.P.A. drainage pan.

Expansion ratio		≥ 7:1
25% drainage time	min/sec	≥ 6'30"

#### Packing Specification

	Plastic Square	Plastic Square	Plastic Cylindrical	Plastic Cylindrical	Ecobulk MX
Capacity	25 litres	5 US gallons	200 litres	55 US gallons	1000 litres
Empty weight (kg)	1.2	0.8	9.0	9.0	70
Filled weight (kg)	30	23	241	250	1230
Dimensions (mm)	448 x 286 x 286	402 x 293 x 240	580 D x 922 H	580 D x 922 H	1200 L x 1000 W x 1160 H
Part number	FN0201GOP	FN0201TOP	FN0201JOP	FN0201WOP	FN0201L8



**EMERGENCY FOAM SERVICE** Call +44 (0) 15242 61166 – 24 hours a day, every day

#### GENERAL SALES

Angus Fire Ltd

Station Road, Bentham, Lancaster, LA2 7NA, UK

Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 261580

Email: [general.enquiries@angusuk.co.uk](mailto:general.enquiries@angusuk.co.uk) • Web: [www.angusfire.co.uk](http://www.angusfire.co.uk)

Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.

© Angus Fire 5094C6/5 10/21  
FP70<sup>®</sup> is a registered trademark of the Angus International group.