



## Alcoseal<sup>C6</sup> 3-6

Alcohol Resistant Film-Forming FluoroProtein (AR-FFFP) Foam Concentrate

- A superior quality Alcohol Resistant Film-Forming FluoroProtein Foam concentrate
- Highly versatile and so eliminates the need to stock a variety of foam types
- Provides stable and long lasting foam blanket - burnback resistance and post-fire security
- Unique formulation provides a tough, cohesive foam blanket with high resistance to heat
- Provides aqueous film over hydrocarbons providing rapid control and extinguishment
- Use in high risk situations where hydrocarbons and polar solvents are processed, stored or transported
- Use at 3% on hydrocarbons and 6% on polar solvents
- UL162 listings
- Compatible with air aspirating and non-aspirating discharge devices
- Readily proportioned using conventional foam proportioning equipment
- Suitable for use with fresh or sea water
- Suitable for use with foam compatible dry powder extinguishing agents



**Alcoseal<sup>C6</sup> 3-6 is a superior quality Alcohol Resistant Film-Forming FluoroProtein (AR-FFFP) fire fighting foam concentrate for extinguishing and securing flammable hydrocarbon and polar solvent liquid fires.**

Its unique formulation is based on advanced protein foam technology. The protein base material provides a tough cohesive foam blanket with high resistance to heat. Fluorochemical surface active agents combined with the protein base produce a vapour-sealing aqueous film on hydrocarbons. On polar solvents an insoluble polymer membrane is formed which protects the foam blanket from the solvent.

- Highly versatile - eliminates the need to stock a variety of foam types.
- Stable and long-lasting foam blanket for excellent burnback resistance and post-fire security.
- Detergent-free for high resistance to fuel pick-up.
- Foam blanket re-seals when ruptured by personnel or equipment.

### Applications

Alcoseal<sup>C6</sup> 3-6 is the ideal fire fighting foam to use in high risk situations where hydrocarbons (such as crude oil, gasoline, diesel fuel, aviation kerosene) and/or polar solvents (such as alcohols, ketones, esters, and ethers) are stored, processed, or transported. It is used extensively by industrial and municipal fire departments.

Alcoseal<sup>C6</sup> 3-6 provides a vapour-suppressing foam blanket on spills of hazardous liquids.

### Approvals and Listings

Alcoseal<sup>C6</sup> 3-6 has numerous approvals and UL Listings against Underwriters Laboratories Standard UL 162 (7th Edition).

Alcoseal<sup>C6</sup> 3-6 passed Lastfire with excellent results.

Independently Tested and Certified to EN1568:2008 Part 3.

### Equipment

Alcoseal<sup>C6</sup> 3-6 is intended for use at 3% (3 parts concentrate to 97 parts of water) on hydrocarbons and 6% on polar solvents.

Alcoseal<sup>C6</sup> 3-6 is readily proportioned using conventional foam proportioning equipment such as in-line foam venturi proportioners, balanced pressure proportioners and around-the-pump proportioners.

Alcoseal<sup>C6</sup> 3-6 can be used with air aspirating discharge devices such as low expansion branchpipes, monitors and top pourer sets.

Exceptional resistance to fuel contamination makes it ideal for forceful application on to hydrocarbon storage tank fires from ground-based mobile monitors.

Alcoseal<sup>C6</sup> 3-6 also produces top quality medium expansion foam.

# Alcoseal<sup>C6</sup> 3-6

## Alcohol Resistant Film-Forming FluoroProtein (AR-FFFP) Foam Concentrate

### Compatibility

Alcoseal<sup>C6</sup> 3-6 is suitable for use in combination with:

- Soft or hard, fresh, brackish or sea water.
- Dry powder extinguishing agents either separately or as twin agent systems.
- Expanded protein-based or synthetic foams for application to a fire in sequence or simultaneously.

### Storage

Alcoseal<sup>C6</sup> 3-6 is exceptionally stable in long-term storage. A shelf-life of at least ten years can be expected if it is stored properly.

### Environment & Disposal

As all 'C6' foams contain PFAS please refer to the product's Safety Data Sheet (SDS) and website for more information regarding the use, discharge and disposal of all firefighting foam products.

### Reliability

Alcoseal<sup>C6</sup> 3-6 is produced to rigorous quality control standards to ensure consistent fire performance and excellent product reliability.

Angus Fire operates a quality management system which complies with the requirements of BS EN ISO 9001.

#### Typical physical properties as supplied

Appearance		Dark Brown Liquid
Specific gravity @ 20°C (68°F)		1.09 - 1.13
pH @ 20°C (68°F)		6.6 - 7.6
<b>Non-Newtonian fluid that is pseudoplastic (shear thinning)</b>		
Viscosity @ 20°C (68°F) using No.4 spindle at 60 rpm	cP	850 - 1750
Maximum continuous storage temperature	°C (°F)	49 (120)
Maximum intermittent storage temperature	°C (°F)	60 (140)
Freezing point	°C (°F)	-10 (14)
Effect of freeze/thaw		No loss of performance
UL Lowest use temperature	°C (°F)	1.7 (35)


#### Typical Foam Properties

Foam generated using the U.K. Defence Standard DEF42-40 5 lpm branchpipe at 7 Bar pressure.  
Foam collected in a 1630 ml N.F.P.A. drainage pan.

Induction rate		3	6
Expansion ratio		≥ 7:1	≥ 8:1
25% drainage time	min/sec	≥ 4' 30"	≥ 10' 30"

#### Packing Specification

	Plastic Square	Plastic Square	Plastic Cylindrical	Plastic Cylindrical	Ecobulk MX
Capacity	25 litres	5 US gallons	200 litres	55 US gallons	1000 litres
Empty weight (kg)	1.2	0.8	9.0	9.0	70
Filled weight (kg)	29	22	227	236	1160
Dimensions (mm)	448 x 286 x 286	402 x 293 x 240	580 D x 922 H	580 D x 922 H	1200 L x 1000 W x 1160 H
Part number	FN0701G0P	FN0701T0P	FN0701J0P	FN0701W0P	FN0701L8



**EMERGENCY FOAM SERVICE** Call +44 (0) 15242 61166 – 24 hours a day, every day

#### GENERAL SALES

##### Angus Fire Ltd

Station Road, Bentham, Lancaster, LA2 7NA, UK  
Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 261580

Email: [general.enquiries@angusuk.co.uk](mailto:general.enquiries@angusuk.co.uk) • Web: [www.angusfire.co.uk](http://www.angusfire.co.uk)

Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.

© Angus Fire 5098C6/4 10/21  
Alcoseal® is a registered trademark of the Angus International group.