

Section 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

Trade name or designation of the mixture	Tridol C6
Registration number	-
Synonyms	Aqueous Film Forming Foam (AFFF)
SDS number	-
Product code	110-35
Date of first issue	19-November-2010
Version number	02
Revision date	03-December-2014
Supersedes date	19-November-2010

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Fire fighting foam concentrate.
Uses advised against	None known.

Details of the supplier of the safety data sheet**Supplier**

Company name	Angus Fire Ltd
Address	Station Road Bentham, Lancashire, LA2 7NA
Phone number:	0044 (0)15 2426 4000
e-mail	general.enquiries@angusuk.co.uk
Contact person	EH&S Manager
Emergency telephone number	0044 (0)15 2426 4000 (Standard office hours: Monday to Friday 8:30am - 4:30pm GMT)

Section 2: Hazards identification**Classification of the substance or mixture****Classification according to Directive 67/548/EEC or 1999/45/EC as amended**

This preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification according to Regulation (EC) No 1272/2008 as amended**Hazard summary**

Physical hazards	Not classified for physical hazards.
Health hazards	Not classified for health hazards. However, occupational exposure to the mixture or substance(s) may cause adverse health effects.
Environmental hazards	Not classified for hazards to the environment.
Specific hazards	May cause skin and eye irritation. May cause mild central nervous system effects.
Main symptoms	Symptoms can include irritation, redness, scratching of the cornea, and tearing. Symptoms may include redness, oedema, drying, defatting and cracking of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Label elements**Label according to Regulation (EC) No. 1272/2008 as amended**

Hazard statements	The substance does not meet the criteria for classification.
--------------------------	--

Precautionary statements

Prevention	Observe good industrial hygiene practices.
Response	If skin irritation occurs: Get medical advice/attention.
Storage	Store away from incompatible materials.

Disposal	Dispose of waste and residues in accordance with local authority requirements.
Supplemental label information	Not applicable.
Other hazards	None known.

Section 3: Composition/information on ingredients

Mixture

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
2-(2-butoxyethoxy)-ethanol	<12	112-34-5 203-961-6	-	603-096-00-8	#
Classification:	DSD: Xi;R36				
	CLP: Eye Irrit. 2;H319				
Water	Balance	7732-18-5 231-791-2	-	-	
Classification:	DSD: -				
	CLP: -				

#: This substance has workplace exposure limit(s).
DSD: Directive 67/548/EEC.
CLP: Regulation No. 1272/2008.

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.
The full text for all R-phrases is displayed in Section 16.

Section 4: First aid measures

Description of first aid measures

Inhalation	Move injured person into fresh air and keep person calm under observation. Get medical attention, if needed.
Skin contact	Wash the skin immediately with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Flush thoroughly with water. If irritation occurs, get medical assistance.
Ingestion	Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions. Only induce vomiting at the instruction of medical personnel.

Most important symptoms and effects, both acute and delayed Exposed may experience eye tearing, redness, and discomfort. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically.

Section 5: Firefighting measures

General fire hazards Product is an extinguishing media. It does not burn or support combustion.

Extinguishing media

Suitable extinguishing media	No specific measures are required as this product is a fire extinguishing medium.
Unsuitable extinguishing media	Not applicable.

Special hazards arising from the substance or mixture Not a fire hazard.

Advice for firefighters

Special protective equipment for firefighters	Self-contained breathing apparatus, operated in positive pressure mode and full protective clothing must be worn in case of fire.
Special firefighting procedures	No specific precautions.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Avoid contact with skin and eyes. Avoid inhalation of mists or aerosols. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.
------------------------------------	--

For emergency responders	Use personal protection recommended in section 8 of the SDS.
Environmental precautions	For large (industrial) releases, prevent spill from entering a waterway.
Methods and material for containment and cleaning up	Absorb spillage with suitable absorbent material. Collect and dispose of spillage as indicated in Section 13.
Reference to other sections	For personal protection, see section 8. For waste disposal, see Section 13.

Section 7: Handling and storage

Precautions for safe handling	Avoid contact with skin and eyes. Wear appropriate personal protective equipment. Wash hands after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in original tightly closed container. Store at temperature below 40°C. Store above freezing. Read and follow manufacturer's recommendations. Store away from incompatible materials.
Specific end use(s)	Fire fighting foam concentrate.

Section 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits

Austria. MAK List

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	MAK	97,5 mg/m3
	STEL	10 ppm
		101,2 mg/m3 15 ppm

Belgium. Exposure Limit Values.

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	STEL	101,2 mg/m3
	TWA	15 ppm
		67,5 mg/m3 10 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	Ceiling	100 mg/m3
	TWA	70 mg/m3

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	VLE	101,2 mg/m3
	VME	15 ppm
		67,5 mg/m3 10 ppm

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	AGW	100 mg/m3

Italy. OELs

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	STEL	101,2 mg/m3
	TWA	15 ppm
		67,5 mg/m3 10 ppm

Netherlands. OELs (binding)

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	STEL	100 mg/m3

Netherlands. OELs (binding)

Components	Type	Value
	TWA	50 mg/m ³

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	TLV	10 ppm 68 mg/m ³

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	STEL	100 mg/m ³
	TWA	67 mg/m ³

Hygiene Norm GN 2.2.5.2439-09. Maximum allowable concentration (MAC) of harmful substances in the air of working zones. Executive No. 76 of 30 april 2006. Including Appendixes No.1, 2, 3 and 4.

Components	Type	Value	Form
2-(2-butoxyethoxy)-ethanol (112-34-5)	Ceiling	10 mg/m ³	Aerosol

Spain. Occupational Exposure Limits

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	STEL	101,2 mg/m ³
	TWA	15 ppm 67,5 mg/m ³ 10 ppm

Sweden. Occupational Exposure Limit Values

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	STEL	200 mg/m ³
	TWA	30 ppm 100 mg/m ³ 15 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	STEL	101,2 mg/m ³
	TWA	15 ppm 67 mg/m ³ 10 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
2-(2-butoxyethoxy)-ethanol (112-34-5)	STEL	101,2 mg/m ³
	TWA	15 ppm 67,5 mg/m ³ 10 ppm

Recommended monitoring procedures Follow standard monitoring procedures.

DNEL Not available.

PNEC Not available.

Exposure controls

Appropriate engineering controls Ensure adequate ventilation, especially in confined areas. Observe occupational exposure limits and minimise the risk of exposure.

Individual protection measures, such as personal protective equipment

General information Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection	Wear approved safety goggles.
Skin protection	
- Hand protection	Wear suitable gloves. Butyl rubber gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.
- Other	Wear suitable protective clothing.
Respiratory protection	In case of inadequate ventilation: Use respiratory equipment with combination filter, type A2/P2.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Handle in accordance with good industrial hygiene and safety practices. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Contain spills and prevent releases and observe national regulations on emissions. Environmental manager must be informed of all major spillages.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Colour	Pale yellow.
Odour	Organic.
Odour threshold	Not available.
pH	6,4 - 7,4 at 20 °C
Melting point/freezing point	Not available.
Boiling point, initial boiling point, and boiling range	100 °C (212 °F) at 760 mmHg
Flash point	> 98 °C (> 208,4 °F)
Auto-ignition temperature	Not applicable.
Flammability (solid, gas)	Not available.
Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Oxidising properties	Not applicable.
Explosive properties	Not applicable.
Explosive limit	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Evaporation rate	Not applicable.
Relative density	1,007
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	No data available.
Decomposition temperature	Not available.
Viscosity	Not available.
Percent volatile	Not available.
Other data	Not available.
Flammability	Not applicable.
Other information	No relevant additional information available.

Section 10: Stability and reactivity

Reactivity	The product is stable and non reactive under normal conditions of use, storage and transport.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Hazardous polymerisation does not occur.
Conditions to avoid	Contact with incompatible materials. Excessive heat. Freezing (Product properties are unaffected).

Incompatible materials	Alkali metals. Strong oxidising agents. Water reactive materials.
Hazardous decomposition products	Carbon oxides. Sulphur oxides. Hydrogen fluoride. Nitrogen oxides (NOx). Magnesium oxides. Sodium oxides.

Section 11: Toxicological information

General information The information in this section is for the individual ingredients that are expected to contribute to the potential health effects of this product.

Information on likely routes of exposure

Ingestion	May cause dizziness, incoordination, headache, nausea, and vomiting.
Inhalation	Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
Skin contact	May cause skin irritation.
Eye contact	May cause eye irritation.

Symptoms Exposed may experience eye tearing, redness, and discomfort. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity May cause skin and eye irritation.

Components

Test results

2-(2-butoxyethoxy)-ethanol (112-34-5)

Acute Dermal LD50 Rabbit: 2700 mg/kg
Acute Oral LD50 Rat: 4500 mg/kg

Skin corrosion/irritation Prolonged or repeated contact may dry skin and cause irritation.

Serious eye damage/eye irritation May cause eye irritation. Exposed may experience eye tearing, redness, and discomfort.

Respiratory sensitisation No data available.

Skin sensitisation Not available.

Germ cell mutagenicity No data available.

Carcinogenicity No data available.

Reproductive toxicity No data available.

Specific target organ toxicity - single exposure No data available.

Specific target organ toxicity - repeated exposure No data available.

Aspiration hazard No data available.

Mixture versus substance information None known.

Other information Persons with pre-existing skin disorders may be more susceptible to the effects of the product.

Section 12: Ecological information

Toxicity

Product

Test results

Tridol C6 (Mixture)

EC50 Water flea (Daphnia magna): 13700 ppm 24 Hours

Persistence and degradability The product is biodegradable. COD: 0,26 gg-1 BOD: 11% / 5 days.

Bioaccumulative potential The product is not expected to bioaccumulate.

Mobility The product is water soluble and may spread in water systems.

Environmental fate - Partition coefficient No data available.

Mobility in soil No data available.

Results of PBT and vPvB assessment Not a PBT or vPvB substance or mixture.

Other adverse effects An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13: Disposal considerations

Waste treatment methods

Residual waste Dispose of waste and residues in accordance with local authority requirements.

Contaminated packaging Dispose of in accordance with local regulations.

EU waste code 16 03 06

Disposal methods/information Dispose of waste and residues in accordance with local authority requirements.

Section 14: Transport information

ADR

The product is not covered by international regulation on the transport of dangerous goods.

RID

The product is not covered by international regulation on the transport of dangerous goods.

ADN

The product is not covered by international regulation on the transport of dangerous goods.

IATA

The product is not covered by international regulation on the transport of dangerous goods.

IMDG

The product is not covered by international regulation on the transport of dangerous goods.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code No information available.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulations

Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 on persistent organic pollutants, Annex I

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V

Not listed.

Directive 96/61/EC concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution Emission Registry (EPER)

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1). Candidate List

Not listed.

Other regulations The product does not need to be labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations Not available.

Chemical safety assessment No Chemical Safety Assessment has been carried out.

Section 16: Other information

List of abbreviations DNEL: Derived No-Effect Level. PNEC: Predicted No-Effect Concentration. PBT: Persistent, bioaccumulative and toxic. vPvB: Very Persistent and very Bioaccumulative.

References US. IARC Monographs on Occupational Exposures to Chemical Agents
EPA: Acquire database
NLM: Hazardous Substances Data Base
ACGIH

Information on evaluation method leading to the classification of mixture The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12.

Full text of any statements or R-phrases and H-phrases under Sections 2 to 15 R36 Irritating to eyes.

H319 - Causes serious eye irritation.

Training information Follow training instructions when handling this material.

Disclaimer

This information is based on our current knowledge and is believed to be correct as of the date issued. The information is intended to describe the product for the purposes of health, safety and environmental requirements only and no warranty, express or implied, is made. It should also not be construed as guaranteeing any specific property of the product. In addition, information obtained from a database is subject to change and may not be as current as the information in the MSDS available directly from Angus Fire.