

SAFETY DATA SHEET

Section 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name or designation

of the mixture

Synonyms

Tridol S6

Registration number

Aqueous Film Forming Foam (AFFF)

Product code 110-05

Date of first issue 05-October-2010

Version number 02

Revision date 03-December-2014 Supersedes date 05-October-2010

Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fire fighting foam concentrate.

Uses advised against None known.

Details of the supplier of the safety data sheet

Supplier

Company nameAngus Fire LtdAddressStation Road

Bentham, Lancashire, LA2 7NA

Phone number: 0044 (0)15 2426 4000

e-mail general.enguiries@angusuk.co.uk

Contact person EH&S Manager

Emergency telephone

0044 (0)15 2426 4000 (Standard office hours: Monday to Friday 8:30am - 4:30pm GMT)

number

SDS number -

Manufacturer/Supplier Angus Fire Ltd

Station Road

Bentham, Lancashire, LA2 7NA general.enquiries@angusuk.co.uk

0044 (0)15 2426 4000

Contact person: EH&S Manager

Emergency 0044 (0)15 2426 4000 (Standard office hours: Monday to Friday 8:30am - 4:30pm GMT)

Section 2: Hazards identification

Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

This preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Serious eye damage/eye irritation Category 2 Causes serious eye irritation.

Hazard summary

Physical hazards Not classified for physical hazards.

Health hazards Not classified for health hazards. However, occupational exposure to the mixture or substance(s)

may cause adverse health effects.

Environmental hazards Not classified for hazards to the environment.

Specific hazards May cause skin irritation. May cause mild central nervous system effects.

Main symptoms Symptoms can include irritation, redness, scratching of the cornea, and tearing. Symptoms may

include redness, oedema, drying, defatting and cracking of the skin. Symptoms of overexposure

may be headache, dizziness, tiredness, nausea and vomiting.

Label elements

Tridol S6

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: 2-(2-butoxyethoxy)-ethanol



Signal word Warning

Hazard statements Causes serious eye irritation.

Precautionary statements

Prevention Wear eye/face protection.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Supplemental label information None.

Other hazards None known.

Section 3: Composition/information on ingredients

Mixture

General information

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
2-(2-butoxyethoxy)-eth	anol	10 - 20	112-34-5 203-961-6	-	603-096-00-8	#
Classification:	DSD:	Xi;R36				
	CLP:	Eye Irrit. 2;H319				
Cocoamido propyl dime	ethylamine	> <3	68155-09-9 268-938-5	-	-	
Classification:	DSD:	Xi;R38-41				
	CLP:	Skin Irrit. 2;H315	5, Eye Dam. 1;H318			
Water		Balance	7732-18-5 231-791-2	-	-	
Classification:	DSD:	-				

^{#:} This substance has workplace exposure limit(s).

CLP: -

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

The full text for all R-phrases is displayed in Section 16.

Section 4: First aid measures

Description of first aid measures

Inhalation Move injured person into fresh air and keep person calm under observation. Get medical

attention, if needed.

Skin contact Wash the skin immediately with soap and water. Get medical attention if irritation develops and

persists.

Eye contact Remove any contact lenses and open eyes wide apart. Get medical attention if irritation develops

and persists.

Ingestion Immediately rinse mouth and drink plenty of water. Keep person under observation. If person

becomes uncomfortable take to hospital along with these instructions. Only induce vomiting at the

instruction of medical personnel.

Most important symptoms and effects, both acute and delayed

Exposed may experience eye tearing, redness, and discomfort. Symptoms may include redness, oedema, drying, defatting and cracking of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Tridol S6 SDS EU

CLP: Regulation No. 1272/2008. DSD: Directive 67/548/EEC.

Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

Section 5: Firefighting measures

General fire hazards Product is an extinguishing media. It does not burn or support combustion.

Extinguishing media

Suitable extinguishing

media

No specific measures are required as this product is a fire extinguishing medium.

Unsuitable extinguishing

media

Special hazards arising from the substance or mixture

Not a fire hazard.

Not applicable.

Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus, operated in positive pressure mode and full protective

clothing must be worn in case of fire.

Special firefighting

procedures

No specific precautions.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Avoid contact with skin and eyes. Avoid inhalation of mists or aerosols. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

For emergency responders

Use personal protection recommended in Section 8 of the SDS.

Environmental precautions

For large (industrial) releases, prevent spill from entering a waterway.

Methods and material for containment and cleaning up Absorb spillage with suitable absorbent material. Collect and dispose of spillage as indicated in

Reference to other sections

For personal protection, see Section 8. For waste disposal, see Section 13.

Section 7: Handling and storage

Precautions for safe handling Avoid contact with skin and eyes. Wear appropriate personal protective equipment. Wash hands

after handling. Observe good industrial hygiene practices. Read and follow manufacturer's

recommendations.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store at temperature below 40°C. Store above freezing.

Store away from incompatible materials.

Specific end use(s)

Fire fighting foam concentrate.

Section 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits

Austria. MAK List

Components	Туре	Value	
2-(2-butoxyethoxy)-ethanol (112-34-5)	MAK	97,5 mg/m3	
	STEL	10 ppm 101,2 mg/m3 15 ppm	
Belgium. Exposure Limit Values.			
Components	Туре	Value	
2-(2-butoxyethoxy)-ethanol (112-34-5)	STEL	101,2 mg/m3	
	TWA	15 ppm 67,5 mg/m3 10 ppm	
Czech Republic. OELs. Governme	ent Decree 361		
Components	Туре	Value	
2-(2-butoxyethoxy)-ethanol (112-34-5)	Ceiling	100 mg/m3	
	TWA	70 mg/m3	

Tridol S6 SDS EU 3/8

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Туре	Value	
VLE	101,2 mg/m3	
VME	15 ppm 67,5 mg/m3	
in the Ambient Air at the Wor	• •	
	Value	
AGW	100 mg/m3	
Туре	Value	
STEL	101,2 mg/m3	
TWA	15 ppm 67,5 mg/m3 10 ppm	
Туре	Value	
STEL	100 mg/m3	
	50 mg/m3	
Туре	Value	
TLV	10 ppm	
and Social Policy Regarding	Maximum Allowable Concentr	ations and Intensities i
Type	Value	
Type STEL	Value 100 mg/m3	
STEL	100 mg/m3	
STEL TWA aximum allowable concentra 2006. Including Appendixes	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4.	
STEL TWA aximum allowable concentra 2006. Including Appendixes Type	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value	Form
STEL TWA aximum allowable concentrar 2006. Including Appendixes Type Ceiling	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4.	
STEL TWA aximum allowable concentrate 2006. Including Appendixes Type Ceiling its	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value 10 mg/m3	Form
STEL TWA aximum allowable concentrar 2006. Including Appendixes Type Ceiling	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value	Form
STEL TWA aximum allowable concentrate 2006. Including Appendixes Type Ceiling its	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value 10 mg/m3 Value 101,2 mg/m3	Form
STEL TWA aximum allowable concentrate 2006. Including Appendixes Type Ceiling its Type	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value 10 mg/m3 Value 101,2 mg/m3 15 ppm 67,5 mg/m3	Form
STEL TWA aximum allowable concentrate 2006. Including Appendixes Type Ceiling its Type STEL	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value 10 mg/m3 Value 101,2 mg/m3 15 ppm	Form
STEL TWA aximum allowable concentrate 2006. Including Appendixes Type Ceiling its Type STEL TWA imit Values	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value 10 mg/m3 Value 101,2 mg/m3 15 ppm 67,5 mg/m3	Form
STEL TWA aximum allowable concentrate 2006. Including Appendixes Type Ceiling its Type STEL TWA imit Values Type	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value 10 mg/m3 Value 101,2 mg/m3 15 ppm 67,5 mg/m3 10 ppm Value	Form
STEL TWA aximum allowable concentrate 2006. Including Appendixes Type Ceiling its Type STEL TWA imit Values Type STEL STEL	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value 10 mg/m3 Value 101,2 mg/m3 15 ppm 67,5 mg/m3 10 ppm Value 200 mg/m3 30 ppm	Form
STEL TWA aximum allowable concentrar 2006. Including Appendixes Type Ceiling its Type STEL TWA imit Values Type STEL TWA TWA	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value 10 mg/m3 Value 101,2 mg/m3 15 ppm 67,5 mg/m3 10 ppm Value 200 mg/m3	Form
STEL TWA aximum allowable concentrate 2006. Including Appendixes Type Ceiling its Type STEL TWA imit Values Type STEL TWA Arbeitsplatz	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value 10 mg/m3 Value 101,2 mg/m3 15 ppm 67,5 mg/m3 10 ppm Value 200 mg/m3 30 ppm 100 mg/m3 15 ppm	Form
STEL TWA aximum allowable concentrar 2006. Including Appendixes Type Ceiling its Type STEL TWA imit Values Type STEL TWA TWA	100 mg/m3 67 mg/m3 tion (MAC) of harmful substan No.1, 2, 3 and 4. Value 10 mg/m3 Value 101,2 mg/m3 15 ppm 67,5 mg/m3 10 ppm Value 200 mg/m3 30 ppm 100 mg/m3	Form
	VLE VME in the Ambient Air at the Wor Type AGW Type STEL TWA Type STEL TWA Contaminants in the Workplat Type TLV	VLE 101,2 mg/m3 VME 15 ppm 67,5 mg/m3 10 ppm in the Ambient Air at the Workplace Type Value AGW 100 mg/m3 Type Value STEL 101,2 mg/m3 TWA 67,5 mg/m3 10 ppm TWA 50 mg/m3 Contaminants in the Workplace Type Value Type Value

Tridol S6
3657 Version No.: 02 Revision date: 03-December-2014

Components	Туре	Value	
	TWA	15 ppm 67 mg/m3 10 ppm	
UK. EH40 Workplace Expos	sure Limits (WELs)		
Components	Туре	Value	
2-(2-butoxyethoxy)-ethanol (112-34-5)	STEL	101,2 mg/m3	
. ,	TWA	15 ppm 67,5 mg/m3 10 ppm	
ommended monitoring cedures	Follow standard monitoring procedures.		
EL .	Not available.		
EC	Not available.		

controls

Appropriate engineering

Ensure adequate ventilation, especially in confined areas. Observe occupational exposure limits

and minimise the risk of exposure.

Individual protection measures, such as personal protective equipment

General information Personal protective equipment should be chosen according to the CEN standards and in

discussion with the supplier of the personal protective equipment.

Eye/face protection Wear approved safety goggles.

Skin protection

- Hand protection Wear suitable gloves. Butyl rubber gloves are recommended. Suitable gloves can be

recommended by the glove supplier.

- Other Wear suitable protective clothing.

Respiratory protection In case of inadequate ventilation: Use respiratory equipment with combination filter, type A2/P2.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Handle in accordance with good industrial hygiene and safety practices. Routinely wash work

clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Contain spills and prevent releases and observe national regulations on emissions.

Environmental manager must be informed of all major spillages.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid. **Form** Liquid.

> Colour Clear pale yellow.

Organic. Odour **Odour threshold** Not available. 6,5 - 8 at 20 °C Ηq -2 °C (28,4 °F) Melting point/freezing

point

Boiling point, initial boiling point, and boiling range

100 °C (212 °F) at 760 mmHg

> 98 °C (> 208,4 °F) Flash point Not applicable. **Auto-ignition temperature** Not available. Flammability (solid, gas)

Flammability limit - lower (%)

Not applicable.

Flammability limit - upper

(%)

Not applicable.

Oxidising properties Not applicable. **Explosive properties** Not applicable. **Explosive limit** Not applicable. Vapour pressure Not applicable.

Tridol S6 SDS EU Vapour density Not applicable. **Evaporation rate** Not applicable.

Relative density 1,01

Solubility (water) Miscible in water. **Partition coefficient** No data available. (n-octanol/water)

Decomposition temperature

Not available

Viscosity

2 cSt

Percent volatile

Not available.

Other data

Flammability

Not applicable.

Other information

No relevant additional information available.

Section 10: Stability and reactivity

Reactivity The product is stable and non reactive under normal conditions of use, storage and transport.

Chemical stability

Conditions to avoid

Stable at normal conditions.

Possibility of hazardous

Hazardous polymerisation does not occur.

reactions

Contact with incompatible materials. Excessive heat. Freezing (Product properties are

unaffected).

Incompatible materials

Alkali metals. Strong oxidising agents. Water reactive materials.

Hazardous decomposition

products

Carbon oxides. Sulphur oxides. Hydrogen fluoride. Nitrogen oxides (NOx). Magnesium oxides.

Sodium oxides.

Section 11: Toxicological information

General information The information in this section is for the individual ingredients that are expected to contribute to

the potential health effects of this product.

Information on likely routes of exposure

May cause dizziness, incoordination, headache, nausea, and vomiting. Ingestion

Inhalation May cause mild central nervous system effects.

May cause skin irritation. Prolonged or repeated skin contact may cause drying, cracking, or Skin contact

irritation

Causes serious eye irritation. Eye contact

Symptoms can include irritation, redness, scratching of the cornea, and tearing. Symptoms may **Symptoms**

include redness, drying and cracking of the skin. Symptoms of overexposure may be headache,

dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity Causes serious eye irritation. May cause skin irritation. May cause mild central nervous system

effects.

Components **Test results**

2-(2-butoxyethoxy)-ethanol (112-34-5) Acute Dermal LD50 Rabbit: 2700 mg/kg

Acute Oral LD50 Rat: 4500 mg/kg

Skin corrosion/irritation

Serious eye damage/eye

May cause skin irritation.

irritation

Causes serious eye irritation.

Respiratory sensitisation

No data available. No data available.

Skin sensitisation

No data available. No data available.

Germ cell mutagenicity Carcinogenicity

No data available.

Specific target organ toxicity - single exposure

Reproductive toxicity

No data available.

Specific target organ

No data available.

toxicity - repeated

exposure

Aspiration hazard No data available.

Tridol S6 SDS FII 6/8

Mixture versus substance

information

None known

Other information

Persons with pre-existing skin disorders may be more susceptible to the effects of the product.

Section 12: Ecological information

Toxicity

Product	Test results
Tridol S6 (Mixture)	LC50 Rainbow trout: 1300 ppm 24 Hours
	LC50 Rainbow trout: > 1800 ppm 3 Hours
	LC50 Rainbow trout: 1300 ppm 48 Hours
	LC50 Rainbow trout: > 1600 ppm 6 Hours
	LC50 Rainbow trout: 1300 ppm 72 Hours
	LC50 Rainbow trout: 1300 ppm 96 Hours

Persistence and degradability

The product is biodegradable. COD: 0,39 gg-1 BOD: 69% / 7 days. BOD: 86 - 94% / 21 days.

BOD: 87-93% / 28 days.

Bioaccumulative potential

The product is not expected to bioaccumulate.

Mobility

The product is water soluble and may spread in water systems.

Environmental fate - Partition coefficient

No data available.

Mobility in soil

No data available.

Results of PBT and vPvB assessment

Not a PBT or vPvB substance or mixture.

Other adverse effects

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Section 13: Disposal considerations

Waste treatment methods

Residual wasteDispose of waste and residues in accordance with local authority requirements.

Contaminated packaging

Dispose of in accordance with local regulations. Empty containers should be taken to an approved

waste handling site for recycling or disposal.

EU waste code

16 03 05* Waste codes should be assigned by the user based on the application for which the

product was used.

Disposal methods/information

Dispose of waste and residues in accordance with local authority requirements.

Section 14: Transport information

ADR

The product is not covered by international regulation on the transport of dangerous goods.

RID

The product is not covered by international regulation on the transport of dangerous goods.

ADN

The product is not covered by international regulation on the transport of dangerous goods.

IATA

The product is not covered by international regulation on the transport of dangerous goods.

IMDG

The product is not covered by international regulation on the transport of dangerous goods.

Transport in bulk according to Annex II of MARPOL73/78 and

No information available.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulations

the IBC Code

Directive 96/61/EC concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution Emission Registery (EPER)

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1). Candidate List

Not listed.

Tridol S6 SDS EU

Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex I

Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V

Regulation (EC) No. 850/2004 on persistent organic pollutants, Annex I

Not listed.

Other regulations The product is classified and labelled in accordance with EC directives or respective national

laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations Follow national regulation for work with chemical agents. **Chemical safety assessment** No Chemical Safety Assessment has been carried out.

Section 16: Other information

List of abbreviations DNEL: Derived No-Effect Level. PNEC: Predicted No-Effect Concentration. PBT: Persistent,

bioaccumulative and toxic. vPvB: Very Persistent and very Bioaccumulative.

References EPA: Acquire database

NLM: Hazardous Substances Data Base

ACGIH

US. IARC Monographs on Occupational Exposures to Chemical Agents

Information on evaluation method leading to the classification of mixture

The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12.

Full text of any statements or R-phrases and H-phrases under Sections 2 to 15

R36 Irritating to eyes. R38 Irritating to skin.

R41 Risk of serious damage to eyes.

H315 - Causes skin irritation.

H318 - Causes serious eve damage. H319 - Causes serious eye irritation.

Training information

Follow training instructions when handling this material.

Disclaimer

This information is based on our current knowledge and is believed to be correct as of the date issued. The information is intended to describe the product for the purposes of health, safety and environmental requirements only and no warranty, express or implied, is made. It should also not be construed as guaranteeing any specific property of the product. In addition, information obtained from a database is subject to change and may not be as current as the information in the

MSDS available directly from Angus Fire.

Tridol S6 SDS FII