



**ANGUS  
FIRE**

# Tridol<sup>C6</sup> S6 LT

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Issue date: 03/02/2017

Revision date: 17/03/2023

Supersedes version of: 16/04/2021

Version: 3.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Tridol<sup>C6</sup> S6 LT  
UFI : QFU0-S07E-S007-420M  
Product code : FNC 03 08  
Type of product : Firefighting foam concentrate (AFFF)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial  
For professional use only  
Use of the substance/mixture : Firefighting foam concentrate

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

ANGUS FIRE Ltd  
Station Road  
LA2 7NA Bentham - United Kingdom  
T +44(0) 1524 264000 - F +44(0)1524 264180  
[general.enquiries@angus.co.uk](mailto:general.enquiries@angus.co.uk) - [www.angusfire.co.uk](http://www.angusfire.co.uk)

#### 1.4. Emergency telephone number

Emergency number : +44(0) 1524 264000 (Standard office hours: Monday to Friday 8:30am - 4:30pm GMT)  
Contact person: EH&S Manager

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302

Specific target organ toxicity – Repeated exposure, Category 2 H373

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS08

Signal word (CLP) : Warning  
Hazardous ingredients : Ethane-1,2-diol  
Hazard statements (CLP) : H302 - Harmful if swallowed.  
H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (if swallowed).  
Precautionary statements (CLP) : P264 - Wash hands thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P301+P312 - IF SWALLOWED: Call a doctor if you feel unwell.  
P314 - Get medical advice/attention if you feel unwell.  
P330 - Rinse mouth.

# Tridol<sup>C6</sup> S6 LT

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

P501 - Dispose in a safe manner in accordance with local/national regulations

### 2.3. Other hazards

Other hazards which do not result in classification : This product contains fluoroalkyl surfactants (which are and include per- or poly- fluoroalkyl substances, "PFAS") and is required to be disposed of by high temperature incineration. See Section 13 for additional information.

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethane-1,2-diol substance with national workplace exposure limit(s) (BE, FR, GB, NL); substance with a Community workplace exposure limit	(CAS-No.) 107-21-1 (EC-No.) 203-473-3 (EC Index-No.) 603-027-00-1 (REACH-no) 01-2119456816-28	25 – 50	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
2-(2-butoxyethoxy)ethanol substance with national workplace exposure limit(s) (BE, FR, GB, NL); substance with a Community workplace exposure limit	(CAS-No.) 112-34-5 (EC-No.) 203-961-6 (EC Index-No.) 603-096-00-8 (REACH-no) 01-2119475104-44	4 – 10	Eye Irrit. 2, H319
2-methyl-2,4-pentanediol substance with national workplace exposure limit(s) (BE, FR, GB)	(CAS-No.) 107-41-5 (EC-No.) 203-489-0 (EC Index-No.) 603-053-00-3 (REACH-no) 01-2119539582-35	0.1 – 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d
2-methyl-2-propanol substance with national workplace exposure limit(s) (BE, FR, GB)	(CAS-No.) 75-65-0 (EC-No.) 200-889-7 (EC Index-No.) 603-005-00-1 (REACH-no) 01-2119444321-51	< 0.05	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Irrit. 2, H319 STOT SE 3, H335
Ethanol substance with national workplace exposure limit(s) (BE, FR, GB, NL)	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5	< 0.05	Flam. Liq. 2, H225 Eye Irrit. 2, H319

Comments : This product contains fluoroalkyl surfactants which are and include PFAS (per- or poly-fluoroalkyl substances), see Sections 13 & 15 for additional information.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion : Rinse mouth. Immediately call a POISON CENTER/doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes damage to organs (kidneys) (if swallowed).

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# Tridol<sup>C6</sup> S6 LT

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : No specific measures are necessary. This product is a fire extinguishing medium.  
Unsuitable extinguishing media : Not applicable.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard.

#### 5.3. Advice for firefighters

Firefighting instructions : Not applicable.  
Protection during firefighting : Not applicable.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

8. Exposure controls/personal protection. 13. Disposal considerations.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Wear recommended personal protective equipment. Read and follow manufacturer's recommendations. Handle in accordance with good industrial hygiene and safety procedures. Read and follow the Safety Data Sheet (SDS) before use. Avoid breathing vapours.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Keep container tightly closed. Store at temperatures not exceeding 60°C (140°F) (intermittent). Protect from sunlight. Protect from freezing. Keep/Store away from incompatible materials.

#### 7.3. Specific end use(s)

Firefighting foam concentrate.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

2-(2-butoxyethoxy)ethanol (112-34-5)		
EU	IOEL TWA	67.5 mg/m <sup>3</sup>
EU	IOEL TWA [ppm]	10 ppm
EU	IOEL STEL	101.2 mg/m <sup>3</sup>
EU	IOEL STEL [ppm]	15 ppm
Belgium	OEL TWA	67.5 mg/m <sup>3</sup>
Belgium	OEL TWA [ppm]	10 ppm
Belgium	OEL STEL	101.2 mg/m <sup>3</sup>
Belgium	OEL STEL [ppm]	15 ppm
France	VME (OEL TWA)	67.5 mg/m <sup>3</sup>
France	VME (OEL TWA) [ppm]	10 ppm
France	VLE (OEL C/STEL)	101.2 mg/m <sup>3</sup>
France	VLE (OEL C/STEL) [ppm]	15 ppm
Netherlands	TGG-8u (OEL TWA)	50 mg/m <sup>3</sup>
Netherlands	TGG-8u (OEL TWA) [ppm]	7.4 ppm
Netherlands	TGG-15min (OEL STEL)	100 mg/m <sup>3</sup>

# Tridol<sup>C6</sup> S6 LT

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>2-(2-butoxyethoxy)ethanol (112-34-5)</b>		
Netherlands	TGG-15min (OEL STEL) [ppm]	15 ppm
United Kingdom	WEL TWA (OEL TWA) [1]	67.5 mg/m <sup>3</sup>
United Kingdom	WEL TWA (OEL TWA) [2]	10 ppm
United Kingdom	WEL STEL (OEL STEL)	101.2 mg/m <sup>3</sup>
United Kingdom	WEL STEL (OEL STEL) [ppm]	15 ppm
USA - ACGIH	ACGIH OEL TWA [ppm]	10 ppm (Inhalable fraction and vapor)
<b>2-methyl-2,4-pentanediol (107-41-5)</b>		
Belgium	OEL TWA	123 mg/m <sup>3</sup>
Belgium	OEL TWA [ppm]	25 ppm
France	VLE (OEL C/STEL)	125 mg/m <sup>3</sup>
France	VLE (OEL C/STEL) [ppm]	25 ppm
United Kingdom	WEL TWA (OEL TWA) [1]	123 mg/m <sup>3</sup>
United Kingdom	WEL TWA (OEL TWA) [2]	25 ppm
United Kingdom	WEL STEL (OEL STEL)	123 mg/m <sup>3</sup>
United Kingdom	WEL STEL (OEL STEL) [ppm]	25 ppm
USA - ACGIH	ACGIH OEL TWA [ppm]	25 ppm (Vapor fraction)
USA - ACGIH	ACGIH OEL STEL	10 mg/m <sup>3</sup> (Inhalable fraction, Aerosol only)
USA - ACGIH	ACGIH OEL STEL [ppm]	50 ppm (Vapor fraction)
<b>Ethane-1,2-diol (107-21-1)</b>		
EU	IOEL TWA	52 mg/m <sup>3</sup>
EU	IOEL TWA [ppm]	20 ppm
EU	IOEL STEL	104 mg/m <sup>3</sup>
EU	IOEL STEL [ppm]	40 ppm
Belgium	OEL TWA	52 mg/m <sup>3</sup>
Belgium	OEL TWA [ppm]	20 ppm
Belgium	OEL STEL	104 mg/m <sup>3</sup>
Belgium	OEL STEL [ppm]	40 ppm
France	VME (OEL TWA)	52 mg/m <sup>3</sup>
France	VME (OEL TWA) [ppm]	20 ppm
France	VLE (OEL C/STEL)	104 mg/m <sup>3</sup>
France	VLE (OEL C/STEL) [ppm]	40 ppm
Netherlands	TGG-8u (OEL TWA)	52 mg/m <sup>3</sup> (damp) 10 mg/m <sup>3</sup> (druppels)
Netherlands	TGG-8u (OEL TWA) [ppm]	20 ppm (damp) 3.9 ppm (druppels)
Netherlands	TGG-15min (OEL STEL)	104 mg/m <sup>3</sup> (damp)
Netherlands	TGG-15min (OEL STEL) [ppm]	40 ppm (damp)
United Kingdom	WEL TWA (OEL TWA) [1]	10 mg/m <sup>3</sup> 52 mg/m <sup>3</sup>
United Kingdom	WEL TWA (OEL TWA) [2]	20 ppm
United Kingdom	WEL STEL (OEL STEL)	104 mg/m <sup>3</sup>
United Kingdom	WEL STEL (OEL STEL) [ppm]	40 ppm
USA - ACGIH	ACGIH OEL TWA [ppm]	25 ppm (Vapor fraction)
USA - ACGIH	ACGIH OEL STEL	10 mg/m <sup>3</sup> (Inhalable fraction, Aerosol only)
USA - ACGIH	ACGIH OEL STEL [ppm]	50 ppm (Vapor fraction)
<b>2-methyl-2-propanol (75-65-0)</b>		
Belgium	OEL TWA	307 mg/m <sup>3</sup>
Belgium	OEL TWA [ppm]	100 ppm
France	VME (OEL TWA)	300 mg/m <sup>3</sup>
France	VME (OEL TWA) [ppm]	100 ppm
United Kingdom	WEL TWA (OEL TWA) [1]	308 mg/m <sup>3</sup>
United Kingdom	WEL TWA (OEL TWA) [2]	100 ppm
United Kingdom	WEL STEL (OEL STEL)	462 mg/m <sup>3</sup>
United Kingdom	WEL STEL (OEL STEL) [ppm]	150 ppm
USA - ACGIH	ACGIH OEL TWA [ppm]	100 ppm
<b>Ethanol (64-17-5)</b>		
Belgium	OEL TWA	1907 mg/m <sup>3</sup>
Belgium	OEL TWA [ppm]	1000 ppm
France	VME (OEL TWA)	1900 mg/m <sup>3</sup>

# Tridol<sup>C6</sup> S6 LT

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethanol (64-17-5)		
France	VME (OEL TWA) [ppm]	1000 ppm
France	VLE (OEL C/STEL)	9500 mg/m <sup>3</sup>
France	VLE (OEL C/STEL) [ppm]	5000 ppm
Netherlands	TGG-8u (OEL TWA)	260 mg/m <sup>3</sup>
Netherlands	TGG-8u (OEL TWA) [ppm]	136 ppm
Netherlands	TGG-15min (OEL STEL)	1900 mg/m <sup>3</sup>
Netherlands	TGG-15min (OEL STEL) [ppm]	992 ppm
United Kingdom	WEL TWA (OEL TWA) [1]	1920 mg/m <sup>3</sup>
United Kingdom	WEL TWA (OEL TWA) [2]	1000 ppm
USA - ACGIH	ACGIH OEL STEL [ppm]	1000 ppm

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure adequate ventilation. Follow the exposure limits given on this material safety data sheet.

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Wear protective gloves (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): nitrile rubber (NBR) - 0.2 mm coating thickness

#### Eye protection:

Sealed safety goggles

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment (recommended filter type A2/P2)



#### Thermal hazard protection:

Wear thermal protective clothing, when necessary.

#### Environmental exposure controls:

Contain spills. Prevent releases. Observe national regulations on emissions. Ensure all national/local regulations are observed.

#### Other information:

Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: 6.6 – 7.6
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: -19 °C
Boiling point	: No data available
Flash point	: > 100 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: No data available

# Tridol<sup>C6</sup> S6 LT

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: 1.02 – 1.06
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 2.9 mm <sup>2</sup> /s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is stable and non reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Incompatible materials. Extremely high or low temperatures.

### 10.5. Incompatible materials

Alkali metals. Oxidizing agent. Water reactive substances.

### 10.6. Hazardous decomposition products

Carbon oxides. Sulphur oxides. Hydrogen fluoride. Nitrogen oxides (NO<sub>x</sub>). Sodium oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

ATE CLP (oral)	1717.033 mg/kg bodyweight
<b>2-(2-butoxyethoxy)ethanol (112-34-5)</b>	
LD50 oral	2410 – 5530 mg/kg bodyweight (Equivalent or similar to OECD 401, Mouse, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	2764 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal, 14 day(s))
<b>2-methyl-2,4-pentanediol (107-41-5)</b>	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Male / female, Experimental value, Oral, 15 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 15 day(s))
LC50 Inhalation - Rat	> 55 mg/l (Equivalent or similar to OECD 403, 8 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))
<b>Ethane-1,2-diol (107-21-1)</b>	
LD50 oral rat	7712 mg/kg bodyweight (according to BASF-internal standards, Rat, Male / female, Experimental value, Aqueous solution, Oral, 7 day(s))
LD50 dermal	> 3500 mg/kg bodyweight (Mouse, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 2.5 mg/l (6 h, Rat, Male / female, Experimental value, Inhalation (aerosol))
<b>2-methyl-2-propanol (75-65-0)</b>	
LD50 oral rat	3046 mg/kg bodyweight (EPA OPPTS 870.1100: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg bodyweight (EU Method B.3: Acute toxicity (dermal), 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 36 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

# Tridol<sup>C6</sup> S6 LT

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 15800 mg/kg bodyweight (Rabbit, Experimental value, Dermal)
LC50 Inhalation - Rat	124.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

Skin corrosion/irritation	: Not classified pH: 6.6 – 7.6
Serious eye damage/irritation	: Not classified pH: 6.6 – 7.6
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs (kidneys) through prolonged or repeated exposure (if swallowed).
Aspiration hazard	: Not classified

Tridol <sup>C6</sup> S6 LT	
Viscosity, kinematic	2.9 mm <sup>2</sup> /s

Potential adverse human health effects and symptoms	: Harmful if swallowed.
---	-------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

2-(2-butoxyethoxy)ethanol (112-34-5)	
LC50 - Fish [1]	1300 mg/l (Equivalent or similar to OECD 203, 96 h, <i>Lepomis macrochirus</i> , Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	> 100 mg/l (EU Method C.2, 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, <i>Desmodesmus subspicatus</i> , Static system, Fresh water, Experimental value, Nominal concentration)

2-methyl-2,4-pentanediol (107-41-5)	
LC50 - Fish [1]	9450 mg/l (Equivalent or similar to OECD 203, 96 h, <i>Oncorhynchus mykiss</i> , Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	5410 mg/l (Equivalent or similar to OECD 202, 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h - Algae [1]	> 429 mg/l (OECD 201: Alga, Growth Inhibition Test, <i>Pseudokirchneriella subcapitata</i> , Static system, Fresh water, Experimental value, Growth rate)

Ethane-1,2-diol (107-21-1)	
LC50 - Fish [1]	> 72860 mg/l (EPA 600/4-90/027, 96 h, <i>Pimephales promelas</i> , Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: <i>Daphnia</i> sp. Acute Immobilisation Test, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value)

2-methyl-2-propanol (75-65-0)	
LC50 - Fish [1]	> 961 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, <i>Pimephales promelas</i> , Flow-through system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	933 mg/l (EU Method C.2, 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 976 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, <i>Pseudokirchneriella subcapitata</i> , Static system, Fresh water, Experimental value, GLP)

Ethanol (64-17-5)	
LC50 - Fish [1]	15300 mg/l (US EPA, 96 h, <i>Pimephales promelas</i> , Flow-through system, Fresh water, Experimental value, Lethal)
EC50 72h - Algae [1]	275 mg/l (Equivalent or similar to OECD 201, <i>Chlorella vulgaris</i> , Static system, Fresh water, Experimental value, Growth rate)

### 12.2. Persistence and degradability

2-(2-butoxyethoxy)ethanol (112-34-5)	
Persistence and degradability	Readily biodegradable in water.

# Tridol<sup>C6</sup> S6 LT

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>2-methyl-2,4-pentanediol (107-41-5)</b>	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.02 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.2 g O <sub>2</sub> /g substance
ThOD	2.3 g O <sub>2</sub> /g substance
<b>Ethane-1,2-diol (107-21-1)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.47 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.24 g O <sub>2</sub> /g substance
ThOD	1.29 g O <sub>2</sub> /g substance
<b>2-methyl-2-propanol (75-65-0)</b>	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	0 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.18 g O <sub>2</sub> /g substance
ThOD	2.59 g O <sub>2</sub> /g substance
<b>Ethanol (64-17-5)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.8 – 0.967 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.7 g O <sub>2</sub> /g substance
ThOD	2.1 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.43
<b>12.3. Bioaccumulative potential</b>	
<b>Tridol<sup>C6</sup> S6 LT</b>	
Bioaccumulative potential	The product is not expected to bioaccumulate.
<b>2-(2-butoxyethoxy)ethanol (112-34-5)</b>	
Partition coefficient n-octanol/water (Log Pow)	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>2-methyl-2,4-pentanediol (107-41-5)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.58 (QSAR, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Ethane-1,2-diol (107-21-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	-1.36 (Experimental value)
Bioaccumulative potential	Not bioaccumulative.
<b>2-methyl-2-propanol (75-65-0)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.317 (Practical experience/observation, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 22.5 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Ethanol (64-17-5)</b>	
BCF - Fish [1]	1 (Other, 72 h, Cyprinus carpio, Static system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	-0.31 (Experimental value)
Bioaccumulative potential	Not bioaccumulative.
<b>12.4. Mobility in soil</b>	
<b>2-(2-butoxyethoxy)ethanol (112-34-5)</b>	
Surface tension	27 mN/m (25 °C, 0.00212 mol/g)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.642 – 1 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
<b>2-methyl-2,4-pentanediol (107-41-5)</b>	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.
<b>Ethane-1,2-diol (107-21-1)</b>	
Surface tension	48.4 mN/m (20 °C)
Ecology - soil	Highly mobile in soil.
<b>2-methyl-2-propanol (75-65-0)</b>	
Surface tension	69.8 mN/m (21 °C, 1.09 g/l, OECD 115: Surface Tension of Aqueous Solutions)



# Tridol<sup>C6</sup> S6 LT

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-methyl-2-propanol (75-65-0)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.324 – 0.707 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
Ethanol (64-17-5)	
Surface tension	22.31 mN/m (20 °C, 100 %)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.2 (log Koc, Experimental value)
Ecology - soil	Highly mobile in soil.

### 12.5. Results of PBT and vPvB assessment

#### Tridol<sup>C6</sup> S6 LT

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

Component	
Ethane-1,2-diol (107-21-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-(2-butoxyethoxy)ethanol (112-34-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methyl-2,4-pentanediol (107-41-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methyl-2-propanol (75-65-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Ethanol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

Other adverse effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

This product contains PFAS. Local requirements for waste disposal may be more restrictive or otherwise different from national regulations. Therefore, applicable local and state regulatory agencies should be contacted regarding disposal of waste foam concentrate or foam/foam solution.

#### Concentrate

Prevent foam concentrate from entering ground water, surface water or storm drains. Small quantities of foam concentrate may be collected on absorbents which can then be disposed of. Disposal should be made in accordance with local, state and federal regulations. High temperature incineration is required at a minimum of 1000°C with a minimum residence time of 2 seconds.

#### Foam/Foam Solution

Prevent foam/foam solution from entering ground water, surface water or storm drains. Small quantities of foam solution may be collected on absorbents which can then be disposed of. Disposal should be made in accordance with local, state and federal regulations. High temperature incineration is required at a minimum of 1000°C with a minimum residence time of 2 seconds.

**NOTE:** Please consult Angus Fire for additional information regarding the disposal of foam concentrates and foam solutions or visit <https://angusfire.co.uk/use-discharge-and-disposal-of-firefighting-foam-products/>.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Ecology - waste materials : Avoid release to the environment.  
European List of Waste (LoW) code : 16 03 05\* - organic wastes containing dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

# Tridol<sup>C6</sup> S6 LT

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

### 14.6. Special precautions for user

#### - Overland transport

Not applicable

#### - Transport by sea

Not applicable

#### - Air transport

Not applicable

#### - Inland waterway transport

Not applicable

#### - Rail transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Listed on REACH Annex XVII (Restriction Conditions). The following restrictions are applicable:

3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	2-methyl-2-propanol ; Ethanol
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Tridol <sup>C6</sup> S6 LT ; 2-(2-butoxyethoxy)ethanol ; 2-methyl-2,4-pentanediol ; Ethane-1,2-diol ; 2-methyl-2-propanol ; Ethanol
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	2-methyl-2-propanol ; Ethanol
55. 2-(2-butoxyethoxy)ethanol (DEGBE)	2-(2-butoxyethoxy)ethanol

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### 15.1.2. National regulations

##### France

Occupational diseases : RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel

##### Germany

Regulatory reference : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : Ethanol is listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : Ethanol is listed

# Tridol<sup>C6</sup> S6 LT

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SZW-lijst van reprotoxische stoffen –  
Vruchtbaarheid : Ethanol is listed

SZW-lijst van reprotoxische stoffen –  
Ontwikkeling : Ethanol is listed

### Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child
H373	May cause damage to organs through prolonged or repeated exposure.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

SDS EU (REACH Annex II) - Angus Fire

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*